



WHERE DO YOU WANT TO RIDE?



ROAD



MIXED SURFACE



TRIATHLON



MOUNTAIN



TRACK



ELECTRIC



ROAD



## PERFORMANCE

AR, FR, DA



## ENDURANCE

VR



## CITY & LIFESTYLE

Verza Cruz, Cruisers



## FITNESS

Verza Speed





ROAD > PERFORMANCE



AR



FR



DA





## AR FRD | ULTIMATE

### FRAME

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert

### FORK

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

48, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Dura-Ace Di2 >](#)

[SRAM RED eTap AXS >](#)

### VIEW

[Geometry Chart >](#)



## AR | ADVANCED

### FRAME

Felt Aero Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert

### FORK

Felt Aero Road UHC Advanced + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

48, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Ultegra Di2 >](#)

[SHIMANO Ultegra >](#)

### VIEW

[Geometry Chart >](#)



## AR FRD

### FRAME

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB30 bottom bracket shell and carbon fiber dropouts, 7075 CNC aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing

### FORK

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

### SIZES

48, 51, 54, 56, 58, 61cm

### WEIGHT

14.6 lb, 6.6 kg

### BUILD KITS

[SHIMANO Dura-Ace Di2 >](#)

### VIEW

[Geometry Chart >](#)



## AR2

### FRAME

Felt Aero Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, BB30 bottom bracket shell and carbon fiber dropouts, 7075 CNC aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing

### FORK

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

### SIZES

48, 51, 54, 56, 58, 61cm

### WEIGHT

16.2 lb, 7.4kg

### BUILD KITS

[SHIMANO Ultegra >](#)

### VIEW

[Geometry Chart >](#)



## AR3

### FRAME

Felt Aero Road UHC Performance carbon fiber, MMC with InsideOut construction, BSA threaded bottom bracket shell, carbon fiber dropouts, replaceable rear derailleur hanger, internal mechanical or internal electronic cable routing

### FORK

Felt Aero Road UHC Advanced carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

### SIZES

48, 51, 54, 56, 58, 61cm

### WEIGHT

16.9 lb, 7.7 kg

### BUILD KITS

[SHIMANO Ultegra >](#)

### VIEW

[Geometry Chart >](#)



## AR5

### FRAME

Felt Aero Road UHC Performance carbon fiber, MMC with InsideOut construction, BSA threaded bottom bracket shell, carbon fiber dropouts, replaceable rear derailleur hanger, internal mechanical or internal electronic cable routing

### FORK

Felt Aero Road UHC Advanced carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube with integrated crown race, crown, blades and dropouts

### SIZES

48, 51, 54, 56, 58, 61cm

### WEIGHT

17.6 lb, 8.0 kg

### BUILD KITS

[SHIMANO 105 >](#)

### VIEW

[Geometry Chart >](#)



## AR FRD | ULTIMATE | FRAME

### FRAME

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert

### FORK

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

48, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## AR | ADVANCED | FRAME

### FRAME

Felt Aero Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert

### FORK

Felt Aero Road UHC Advanced + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

48, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## FR FRD | ULTIMATE

### FRAME

Felt Race Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

### FORK

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

43, 47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Dura-Ace Di2 >](#)

### VIEW

[Geometry Chart >](#)



## FR | ADVANCED

### FRAME

Felt Race Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

### FORK

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

43, 47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Ultegra Di2 >](#)

[SHIMANO Ultegra >](#)

[SHIMANO 105 >](#)

### VIEW

[Geometry Chart >](#)





## FR | PERFORMANCE | RIM BRAKE

### FRAME

Felt Race Road UHC Performance carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, carbon fiber dropouts, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

### FORK

Felt Race Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

### SIZES

51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Ultegra >](#)

### VIEW

[Geometry Chart >](#)



## FR | PERFORMANCE | RIM BRAKE

### FRAME

Felt Race Road UHC Performance carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, carbon fiber dropouts, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

### FORK

Felt Race Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

### SIZES

51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO 105 >](#)

### VIEW

[Geometry Chart >](#)



## FR | 30

### FRAME

Felt Race Road SuperLite custom butted aluminum, Dynaform smooth welded construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger

### FORK

Felt Race Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

43, 47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO 105 >](#)

### VIEW

[Geometry Chart >](#)



## FR FRD | ULTIMATE | FRAME

### FRAME

Felt Race Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing, 27.2mm seatpost size

### FORK

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

43, 47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## FR FRD | ULTIMATE, RIM BRAKE | FRAME

### FRAME

Felt Race Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, carbon fiber dropouts, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing, 27.2mm seatpost size

### FORK

Felt Race Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown, blades and dropouts. Integrated compression device

### SIZES

43, 47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## FR | ADVANCED | FRAME

### FRAME

Felt Race Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing, 27.2mm seatpost size

### FORK

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

43, 47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## DA | ADVANCED | FRAME

### FRAME

Felt Defined Aero TT/Tri UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, BB30 bottom bracket shell, horizontal dropouts with integrated dropout adjusters, fully integrated proprietary braking system, internal mechanical or electronic cable routing

### FORK

Felt Bayonet 4 UHC Ultimate + TeXtreme carbon fiber monocoque construction, carbon fiber brake cover, blades, dropouts and crown with Felt compression device

### SIZES

51, 54, 56, 58cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## VR | ADVANCED

### FRAME

Felt Variable Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

### FORK

Felt Variable Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

43, 47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Ultegra Di2 >](#)

[SHIMANO 105 >](#)

### VIEW

[Geometry Chart >](#)



## VR | PERFORMANCE

### FRAME

Felt Variable Road UHC Performance carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

### FORK

Felt Variable Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Ultegra >](#)

### VIEW

[Geometry Chart >](#)



## VR | PERFORMANCE

### FRAME

Felt Variable Road UHC Performance carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

### FORK

Felt Variable Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO 105 >](#)

### VIEW

[Geometry Chart >](#)



## VR | 40

### FRAME

Felt Variable Road Disc FLite custom butted aluminum, hydroform smooth welded construction, BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

### FORK

Felt Variable Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Tiagra >](#)

### VIEW

[Geometry Chart >](#)



## VR | 60

### FRAME

Felt Variable Road Disc FLite custom butted aluminum, hydroform smooth welded construction, BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

### FORK

Felt Variable Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Claris >](#)

### VIEW

[Geometry Chart >](#)



## VR | ADVANCED | FRAME

### FRAME

Felt Variable Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing, 27.2mm seatpost size

### FORK

Felt Variable Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

43, 47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



TRACK



TA





## TA FRD | ULTIMATE | FRAME

### FRAME

Felt Track Aero, UHC Ultimate + TeXtreme carbon fiber

### FORK

Felt TA FRD, UHC Ultimate + TeXtreme carbon fiber

### SIZES

55cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)



TRIATHLON



IA



IB





## IA FRD DISC

### FRAME

Felt Integrated Aero Tri Disc UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

### FORK

Felt Dagger Disc UHC Ultimate + TeXtreme carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

### SIZES

48, 51, 54, 56, 58cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Dura-Ace Di2 >](#)

### VIEW

[Geometry Chart >](#)



## IA | ADVANCED

### FRAME

Felt Integrated Aero Tri Disc UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

### FORK

Felt Dagger Disc UHC Advanced carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

### SIZES

48, 51, 54, 56, 58cm

### WEIGHT

n/a

### BUILD KITS

[SRAM Force eTap AXS >](#)

[SHIMANO Ultegra Di2 >](#)

[SHIMANO Ultegra >](#)

### VIEW

[Geometry Chart >](#)



## IA | ADVANCED | RIM BRAKE

### FRAME

Felt Integrated Aero Tri UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, horizontal dropouts with integrated dropout adjusters, aerodynamically optimized for direct mount rear brake, internal mechanical or electronic cable routing

### FORK

Felt IA UHC Advanced carbon fiber monocoque construction, 1.125" carbon fiber steerer, blades, dropouts, crown; aerodynamically optimized for a conventional brake

### SIZES

48, 51, 54, 56, 58cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO 105 >](#)

### VIEW

[Geometry Chart >](#)



## FRAME IA FRD DISC

### FRAME

Felt Integrated Aero Tri Disc UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

### FORK

Felt Dagger Disc UHC Ultimate + TeXtreme carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

### SIZES

48, 51, 54, 56, 58cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## IA FRD | ADVANCED, SYSTEM | FRAME

### FRAME

Felt Integrated Aero Tri Disc UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

### FORK

Felt Dagger Disc UHC Advanced + TeXtreme carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

### SIZES

48, 51, 54, 56, 58cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## B14

### FRAME

Felt Aero TT/Tri UHC Performance carbon fiber, MMC with InsideOut construction, BB30 bottom bracket shell, horizontal dropouts with integrated dropout adjusters, internal mechanical or electronic cable routing

### FORK

Felt Aero TT/Tri UHC Performance carbon fiber blades and dropouts, 1.125" aluminum steerer tube

### SIZES

47cm (650c), 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Ultegra >](#)

### VIEW

[Geometry Chart >](#)



MIXED SURFACE



CYCLOCROSS  
FX



GRAVEL  
Breed



ADVENTURE  
Broom





## FX | ADVANCED+

### FRAME

Felt Cyclocross UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, shoulder friendly top tube, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

### FORK

Felt Cyclocross UHC Ultimate + TeXtreme carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" carbon fiber steerer tube, integrated crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

47, 50, 53, 55, 57, 60cm

### WEIGHT

n/a



### BUILD KITS

[SRAM Force Cx1 >](#)

[SHIMANO GRX 800 >](#)

### VIEW

[Geometry Chart >](#)



## FX | ADVANCED

### FRAME

Felt Cyclocross UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, shoulder friendly top tube, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

### FORK

Felt Cyclocross UHC Advanced + TeXtreme carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, carbon fiber blades, flat mount disc standard, 12 x 100mm thru axle

### SIZES

47, 50, 53, 55, 57, 60cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO GRX 600 >](#)

### VIEW

[Geometry Chart >](#)



## FX FRD | ULTIMATE | FRAME

### FRAME

Felt Cyclocross UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, shoulder friendly top tube, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing, 27.2mm seatpost size

### FORK

Felt Cyclocross UHC Ultimate + TeXtreme carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" carbon fiber steerer tube, integrated crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

47, 50, 53, 55, 57, 60cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## FX | ADVANCED+ | FRAME

### FRAME

Felt Cyclocross UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, shoulder friendly top tube, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing, 27.2mm seatpost size

### FORK

Felt Cyclocross UHC Ultimate + TeXtreme carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" carbon fiber steerer tube, integrated crown and blades. Flat mount disc standard, 12 x 100mm thru axle

### SIZES

47, 50, 53, 55, 57, 60cm

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## BREED | 20

### FRAME

Felt Gravel Race Disc Superlite custom butted aluminum, hydroform smooth welded construction, T47 86 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

### FORK

Felt Adventure Gravel UHC Advanced carbon fiber full monocoque construction, ControlTaper 1.125" - 1.5" carbon steerer tube, flat mount disc standard, 12 x 100mm thru axle with fender mounts

### SIZES

47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SRAM Force Cx1 >](#)

### VIEW

[Geometry Chart >](#)



## BREED | 30

### FRAME

Felt Gravel Race Disc Superlite custom butted aluminum, hydroform smooth welded construction, T47 86 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

### FORK

Felt Adventure Gravel UHC Advanced carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, flat mount disc standard, 12 x 100mm thru axle with fender mounts

### SIZES

47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO GRX600 >](#)

### VIEW

[Geometry Chart >](#)



## BROAM | 30

### FRAME

Felt Adventure Road Disc Superlite custom butted aluminum, smooth welded construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

### FORK

Felt Adventure Gravel UHC Advanced carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, flat mount disc standard, 12 x 100mm thru axle with mid-mount rack and fender mounts

### SIZES

47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO GRX600 >](#)

### VIEW

[Geometry Chart >](#)





## BROAM | 40

### FRAME

Felt Adventure Road Disc Superlite custom butted aluminum, smooth welded construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

### FORK

Felt Adventure Gravel UHC Advanced carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, flat mount disc standard, 12 x 100mm thru axle with mid-mount rack and fender mounts

### SIZES

47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Tiagra >](#)

### VIEW

[Geometry Chart >](#)



## BROAM | 60

### FRAME

Felt Adventure Road Disc Superlite custom butted aluminum, smooth welded construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

### FORK

Felt Adventure Gravel UHC Advanced carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, flat mount disc standard, 12 x 100mm thru axle with mid-mount rack and fender mounts

### SIZES

47, 51, 54, 56, 58, 61cm

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Claris >](#)

### VIEW

[Geometry Chart >](#)





MOUNTAIN



## CROSS COUNTRY

Edict, Doctrine, Dispatch



## TRAIL

Virtue, Decree



## ENDURO

Compulsion



## FAT BIKE

DD





MOUNTAIN > CROSS COUNTRY



EDICT



DOCTRINE



DISPATCH





## EDICT FRD | ULTIMATE

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

FOX DPS Float, dual lockout remote, 190 x 40mm Trunnion

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SHIMANO XTR >](#)

### VIEW

[Geometry Chart >](#)



## EDICT | ADVANCED

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

FOX DPS Performance Elite Float, 190 x 40mm Trunnion

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SHIMANO XT >](#)

[SHIMANO SLX >](#)

[SRAM NX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## EDICT FRD

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

RockShox SID, World Cup Debonair with Charger 2, 100mm travel, OneLoc full sprint, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SRAM XX1 Eagle >](#)

### VIEW

[Geometry Chart >](#)



## EDICT I

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

RockShox SID RL Debonair with Charger 2, 100mm travel, remote, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SRAM X01 >](#)

### VIEW

[Geometry Chart >](#)



## EDICT 3

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleuer hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleuer cable routing

### FORK

RockShox Reba RL Solo air with Motion Control, 120mm travel, remote, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SRAM GX >](#)

### VIEW

[Geometry Chart >](#)



## EDICT 5

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

RockShox Recon RL Solo air, Remote, 120mm travel, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SRAM NX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## EDICT FRD | ULTIMATE | FRAME

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing, Ø30.9 seat post size

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## EDICT | ADVANCED | FRAME

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing, Ø30.9 seat post size

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## EDICT FRD FRAME

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing, Ø30.9 seat post size

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## EDICT 1 FRAME

### FRAME

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing, Ø30.9 seat post size

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## DOCTRINE | ADVANCED

### FRAME

Felt XC, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, low-direct front derailleur mount, replaceable derailleur hanger, flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

FOX 32 Step-Cast Performance Elite, 120mm travel, lockout remote, 15 x 110mm Boost thru axle

### SIZES

XS (14"), SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SHIMANO XT >](#)

[SHIMANO SLX >](#)

### VIEW

[Geometry Chart >](#)



## DOCTRINE | PERFORMANCE

### FRAME

Felt XC, UHC Performance carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, low-direct front derailleur mount, replaceable derailleur hanger, flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

RockShox Recon RL, 100mm travel, lockout remote, 15 x 110mm Boost thru axle

### SIZES

XS (14"), SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SRAM NX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## DOCTRINE 1

### FRAME

Felt XC, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, Kevlar chain watcher, replaceable derailleur hanger, flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

RockShox Sid RL Debonair with Charger 2, 100mm travel, OneLoc remote, 15 x 110mm Boost thru axle

### SIZES

XS (14"), SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SRAM X01 Eagle >](#)

### VIEW

[Geometry Chart >](#)



## DOCTRINE 3

### FRAME

Felt XC, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, Kevlar chain watcher, replaceable derailleur hanger, flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

RockShox Reba RL Solo Air with Motion Control, 100mm travel, OneLoc remote, 15 x 110mm Boost thru axle

### SIZES

XS (14"), SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SRAM GX >](#)

### VIEW

[Geometry Chart >](#)



## DOCTRINE 5

### FRAME

Felt XC, UHC Performance carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, Kevlar chain watcher, replaceable derailleur hanger, flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

### FORK

RockShox Recon RL Solo Air, 100mm travel, OneLoc remote, 15 x 110mm Boost thru axle

### SIZES

XS (14"), SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SRAM NX >](#)

### VIEW

[Geometry Chart >](#)



## DISPATCH 9 / 60

### FRAME

Felt XC, SuperLite aluminum, hydroform, ControlTaper head tube, replaceable derailleur hanger, IS disc mounts, 73mm threaded BB, 135mm OLD

### FORK

RockShox 30 Silver TK, 100mm travel, tapered steerer

### SIZES

XS (14"), SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SRAM SX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## DISPATCH 9 / 70

### FRAME

Felt XC, F-Lite aluminum, hydroform, replaceable derailleur hanger, IS disc mounts, 73mm threaded BB, 135mm OLD

### FORK

SR/Suntour XCM-HLO, 100mm travel, preload, hydraulic lockout

### SIZES

XS (14"), SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## DISPATCH 9 / 80

### FRAME

Felt XC, F-Lite aluminum, hydroform, replaceable derailleur hanger, IS disc mounts, 73mm threaded BB, 135mm OLD

### FORK

SR/Suntour XCT-HLO, 100mm travel, preload, hydraulic lockout

### SIZES

XS (14"), SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



MOUNTAIN > TRAIL



VIRTUE



DECREE





## VIRTUE | ADVANCED

### FRAME

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleuer hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleuer cable/brake hose/dropper post routing

### FORK

FOX 36 Float Performance Elite, 140mm travel, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SHIMANO XT >](#)

[SHIMANO SLX >](#)

[SRAM NX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## VIRTUE | ADVANCED | FRAME

### FRAME

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

### FORK

FOX 36 Float Performance, 140mm travel, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## DECREE FRD

### FRAME

Felt Trail, 140mm travel, FAST suspension, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

### FORK

RockShox Pike RCT3 Debonair with Charger 2, 150mm travel, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

28.48 lb, 12.92 kg

### BUILD KITS

[SRAM XX1 Eagle >](#)

### VIEW

[Geometry Chart >](#)



## DECREE I

### FRAME

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

### FORK

RockShox Pike RC Debonair with Charger 2, 150mm travel, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

28.61 lb, 12.98 kg

### BUILD KITS

[SRAM X01 Eagle >](#)

### VIEW

[Geometry Chart >](#)



## DECREE 3

### FRAME

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

### FORK

RockShox Revelation RC with Charger, 150mm travel, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

30.9 lb, 14.02 kg

### BUILD KITS

[SRAM GX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## DECREE 5

### FRAME

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

### FORK

RockShox REBA RL with Motion Control, 150mm travel, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

31.7 lb, 14.38 kg

### BUILD KITS

[SRAM NX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## DECREE | FRAME

### FRAME

Felt Trail, UHC Advanced carbon fiber, MMC with InsideOut construction, Full carbon dropouts, 140mm travel, FAST suspension, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber trunnion rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing, Ø30.9mm seat post size

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

5.84 lb, 2.65 kg

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## COMPULSION I

### FRAME

Felt All Mountain, 165mm travel, Equilink suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

### FORK

FOX Performance Elite 36, 170mm travel, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

31.1 lb, 14.11 kg

### BUILD KITS

[SRAM GX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## COMPULSION 3

### FRAME

Felt All Mountain, 165mm travel, Equilink suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

### FORK

FOX Performance 36, 170mm travel, 15 x 110mm Boost thru axle

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

32.6 lb, 14.79 kg

### BUILD KITS

[SRAM NX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## COMPULSION 1 FRAME

### FRAME

Felt All Mountain, UHC Advanced carbon fiber, MMC with InsideOut construction, Full carbon dropouts, 170mm travel, Equilink suspension, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber trunnion rocker links, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing, Ø30.9mm seat post size

### SIZES

SM (16"), MD (18"), LG (20"), XL (22")

### WEIGHT

7.07 lb, 3.21 kg

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## DD | 30

### FRAME

Felt Fat, SuperLite aluminum, hydroform, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, clamp adaptor for high direct type front derailleur mount

### FORK

Felt Fat hydroformed 6061 aluminum, tapered steerer, post-mount disc, rack mounts, 15 x 150mm thru axle

### SIZES

XS (14"), SM (16"), MD (18"), LG (20")

### WEIGHT

n/a

### BUILD KITS

[SHIMANO SLX >](#)

### VIEW

[Geometry Chart >](#)



## DD | 70

### FRAME

Felt Fat, SuperLite aluminum, hydroform, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, clamp adaptor for high direct type front derailleur mount

### FORK

Felt Fat hydroformed 6061 aluminum, tapered steerer, post-mount disc, rack mounts, 15 x 150mm thru axle

### SIZES

XS (14"), SM (16"), MD (18"), LG (20")

### WEIGHT

n/a

### BUILD KITS

[SRAM NX Eagle >](#)

### VIEW

[Geometry Chart >](#)



## Q20-S

### FRAME

Felt Q Kids Series, Dynaform 6061 aluminum, 1-1/8" head tube, forged dropouts, standard 68mm bottom bracket, 135mm OLD, Ø27.2mm seatpost, Ø31.8mm front derailleur clamp

### FORK

SR Suntour M3010, 40mm travel

### SIZES

20"

### WEIGHT

n/a



### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## Q24

### FRAME

Felt Q Kids Series, Dynaform 6061 aluminum, 1-1/8" head tube, forged dropouts, standard 68mm bottom bracket, 135mm OLD, Ø27.2mm seatpost, Ø31.8mm front derailleur clamp

### FORK

SR Suntour XCT JR, 50mm travel

### SIZES

24"

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## Q24 DISC

### FRAME

Felt Q Kids Series, Dynaform 6061 aluminum, 1-1/8" head tube, forged dropouts, IS disc mounts, standard 68mm bottom bracket, 135mm OLD, Ø27.2mm seatpost, Ø31.8mm front derailleur clamp

### FORK

SR Suntour XCT JR, 50mm travel

### SIZES

24"

### WEIGHT

n/a

### BUILD KITS

[See Full Technical Specifications >](#)

### VIEW

[Geometry Chart >](#)



## MOUNTAIN

Redemption, Surplus





## REDEMPTION | 30

### FRAME

Felt All Mountain, 150mm travel, Shimano e-Bike specific, double-butted 6061 aluminum, fully integrated down tube, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, 12 x 148mm Syntace style thru axle

### FORK

Rock Shox Yari RC Debonair, 150mm travel, 15 x 110mm Boost, E-Bike specific

### SIZES

S (16"), M (18"), L (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SHIMANO SLX >](#)





## REDEMPTION | 50

### FRAME

Felt All Mountain, 150mm travel, Shimano e-Bike specific, double-butted 6061 aluminum, fully integrated down tube, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, 12 x 148mm Syntace style thru axle

### FORK

Rock Shox Sektor Debonair, 150mm travel, 15 x 110mm Boost, E-Bike specific

### SIZES

S (16"), M (18"), L (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Deore >](#)



## SURPLUS | 50

### FRAME

Felt 27.5+, Shimano e-bike design, 6061 aluminum, fully integrated down tube, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, 12 x 148mm Syntace style thru axle

### FORK

RockShox Recon RL Solo Air, 130mm travel, 15 x 110mm Boost, E-Bike specific

### SIZES

S (16"), M (18"), L (20"), XL (22")

### WEIGHT

n/a

### BUILD KITS

[SHIMANO Deore >](#)

**AR FRD | Ultimate | Dura-Ace Di2**
**Frame**

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert.

**Fork**

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, and blades. Flat mount disc standard, 12 x 100mm thru axle

**Headset**

FSA integrated sealed cartridge bearings MR121 (870E-RS) Upper bearing and MR168 (970E-RS) lower bearing with integrated aero headset spacers and integrated top cover for use with non-integrated stem

**Stem**

AR integrated carbon with internal cable and hose routing -6° rise, Ø31.8mm, 48 - 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

**Handlebar**

Pro Components Vibe Aero, Ø31.8mm, 48 - 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

**Grips**

Felt VelvetGel tape with 3M reflective base with Felt Bubble-Tech F-Wing bar end plugs

**Shifters**

Shimano Dura-Ace Di2 R9170 11-speed

**Front Derailleur**

Shimano Dura-Ace R9150 Di2 braze-on

**Rear Derailleur**

Shimano Dura-Ace R9150 Di2 11-speed short cage

**Crankset**

Shimano Dura-Ace R9100, 52/36T, 43 - 47cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

**Bottom Bracket**

Ceramic Speed BB386 with 24mm bearings

**Chain**

Shimano Dura-Ace 11-speed

**Freewheel / Cassette**

Shimano Dura-Ace 11-speed, 11-28T

**Brake Levers**

Shimano Dura-Ace R9170, hydraulic

**Brake (Front)**

Shimano Dura-Ace R9170 hydraulic disc, 160mm rotor

**Brake (Rear)**

Shimano Dura-Ace R9170 hydraulic disc, 140mm rotor

**Saddle**

Prologo Dimension Nack

**Seatpost**

Felt VariMount Aero Road UHC Advanced + TeXtreme carbon fiber with high-frequency vibration reducing insert, integrated battery holder, 350mm length\*, 0/20mm offset

\*Seatpost can be cut to length

**Seatpost Clamp**

Felt Internaloc integrated with titanium bolts

**Rims / Wheelset**

Zipp 454 NSW Carbon Clincher Disc-brake, tubeless compatible

**Front Hub**

Zipp Cognition Disc Brake, 12 x 100mm thru axle

**Rear Hub**

Zipp Cognition Disc Brake, 11-speed, 12 x 142mm thru axle

**Thru Axles**

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 161 (161L + 9 head = 170 total), thread: M12 x 1.0P x 18L, Syntace

**Spokes**

CX-Ray - Black

**Tires**

Continental Grand Prix 5000 Tubeless, 700 x 25c

**Accessories**

Carbon assembly paste, chain plate protector, valve extenders, aero seatpost slot covers, Di2 battery charger, and headset top cover for use with non-integrated stem



## AR FRD | Ultimate | RED eTap AXS

## Frame:

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert.

## Fork:

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25"" carbon fiber steerer tube, integrated crown race, crown, and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearings MR121 (870E-RS) Upper bearing and MR168 (970E-RS) lower bearing with integrated aero headset spacers and integrated top cover for use with non-integrated stem

## Stem:

AR integrated carbon with internal cable and hose routing -6° rise, Ø31.8mm, 48 - 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Zipp SL-70 Aero, Ø31.8mm, 48cm: 380mm, 51cm: 40cm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt VelvetGel tape with 3M reflective base with Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

SRAM RED eTap AXS HRD 12-speed

## Front Derailleur:

SRAM RED eTap AXS braze-on

## Rear Derailleur:

SRAM RED eTap AXS 12-speed

## Crankset:

SRAM Red DUB, 48/35T, 48cm: 167.5mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

CeramicSpeed BB386 DUB

## Chain:

SRAM Red 12-speed

## Freewheel / Cassette:

SRAM XG 1290 12-speed, 10-28T

## Brake Levers:

SRAM RED eTap AXS HRD, hydraulic

## Brake (Front):

SRAM RED eTap AXS HRD, 160mm rotor

## Brake (Rear):

SRAM RED eTap AXS HRD, 140mm rotor

## Saddle:

Prologo Dimension Nack

## Seatpost:

Felt VariMount Aero Road UHC Advanced + TeXtreme carbon fiber with high-frequency vibration reducing insert, integrated battery holder, 350mm length\*, 0/20mm offset

\*Seatpost can be cut to length

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Rims / Wheelset:

Zipp 454 NSW carbon clincher disc-brake, tubeless compatible

## Front Hub:

Zipp Cognition Disc Brake, 12 x 100mm thru axle

## Rear Hub:

Zipp Cognition Disc Brake, 11-speed, 12 x 142mm thru axle

## Thru Axles:

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 161 (161L + 9 head = 170 total), thread: M12 x 1.0P x 18L, Syntace

## Spokes:

CX-Ray - Black

## Tires:

Continental Grand Prix 5000 Tubeless, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector, valve extenders, aero seatpost slot covers, Di2 battery charger, and headset top cover for use with non-integrated stem



## AR | Advanced | Ultegra Di2

## Frame:

Felt Aero Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert.

## Fork:

Felt Aero Road UHC Advanced + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearings MR121 (870E-RS) Upper bearing and MR168 (970E-RS) lower bearing with integrated aero headset spacers and integrated top cover for use with non-integrated stem

## Stem:

AR integrated carbon with internal cable and hose routing -6° rise, Ø31.8mm, 48 - 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Carbon Aero, 80mm reach, 125mm drop, Ø31.8mm, 48 - 54cm: 400mm, 56 - 61cm: 420mm

## Grips:

Felt VelvetGel tape with 3M reflective base with Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Ultegra Di2 R8070 11-speed

## Front Derailleur:

Shimano Ultegra R8050 Di2 braze-on

## Rear Derailleur:

Shimano Ultegra R8050 Di2 11-speed short cage

## Crankset:

Shimano Ultegra R8000, 52/36T, 48cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Token BB386 with 24mm bearings

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-30T

## Brake Levers:

Shimano Ultegra R8070, hydraulic

## Brake (Front):

Shimano BR-R8070 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano BR-R8070 hydraulic disc, 140mm rotor

## Saddle:

Prologo Dimension T4.0

## Seatpost:

Felt VariMount Aero Road UHC Advanced + TeXtreme carbon fiber with high-frequency vibration reducing insert, integrated battery holder, 350mm length\*, 0/20mm offset

\*Seatpost can be cut to length

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Rims / Wheelset:

Reynolds AR58 DB Custom carbon, tubeless ready, 21mm inner width, 58mm depth

## Front Hub:

Reynolds Series 1, straight-pull design, 12 x 100mm thru axle, Center Lock

## Rear Hub:

Reynolds Series 1, straight-pull design, 4 pawl, 24T ratchet, 11-speed, 12 x 142mm thru axle, Center Lock

## Thru Axles:

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 161 (161L + 9 head = 170 total), thread: M12 x 1.0P x 18L, Syntace

## Spokes:

Sapim Sprint bladed

## Tires:

Continental Grand Prix 5000 folding, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector, tubeless valve stems, aero seatpost slot covers, Di2 battery charger, and headset top cover for use with non-integrated stem

## AR | Advanced | Ultegra

## Frame:

Felt Aero Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert.

## Fork:

Felt Aero Road UHC Advanced + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearings MR121 (870E-RS) Upper bearing and MR168 (970E-RS) lower bearing with integrated aero headset spacers and integrated top cover for use with non-integrated stem

## Stem:

AR integrated carbon with internal cable and hose routing -6° rise, Ø31.8mm, 48 - 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Carbon Aero, 80mm reach, 125mm drop, Ø31.8mm, 48 - 54cm: 400mm, 56 - 61cm: 420mm

## Grips:

Felt VelvetGel tape with 3M reflective base with Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Ultegra R8020 11-speed

## Crankset:

Shimano Ultegra R8000, 52/36T, 48cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Token BB386 with 24mm bearings

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-30T

## Brake Levers:

Shimano Ultegra R8020, hydraulic

## Brake (Front):

Shimano BR8070 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano BR8070 hydraulic disc, 140mm rotor

## Saddle:

Prologo Dimension T4.0

## Seatpost:

Felt VariMount Aero Road UHC Advanced + TeXtreme carbon fiber with high-frequency vibration reducing insert, integrated battery holder, 350mm length\*, 0/20mm offset

\*Seatpost can be cut to length

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Rims / Wheelset:

Reynolds AR58 DB Custom carbon, tubeless ready, 21mm inner width, 58mm depth

## Front Hub:

Reynolds Series 1, straight-pull design, 12 x 100mm thru axle, Center Lock

## Rear Hub:

Reynolds Series 1, straight-pull design, 4 pawl, 24T ratchet, 11-speed, 12 x 142mm thru axle, Center Lock

## Thru Axles:

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 161 (161L + 9 head = 170 total), thread: M12 x 1.0P x 18L, Syntace

## Spokes:

Sapim Sprint bladed

## Tires:

Continental Grand Prix 5000 folding, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector, tubeless valve stems, aero seatpost slot covers, Di2 battery charger, and headset top cover for use with non-integrated stem



## AR FRD

## Frame:

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB30 bottom bracket shell and carbon fiber dropouts, 7075 CNC aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing

## Fork:

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

## Headset:

FSA integrated sealed cartridge bearing with SL Ceramic, aluminum cased ACB upper and lower bearings, carbon fiber headset spacers, No.44/CF-R, 1.125"" - 1.25""

## Stem:

Pro Components Vibe -10° rise, Ø31.8mm, 48cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Pro Components Vibe Aero, Ø31.8mm, 48 - 54cm: 400mm, 56 - 61cm: 420mm

## Grips:

Felt VelvetGel tape with 3M reflective base with Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Dura-Ace R9150 Di2 11-speed with secondary sprint shifters

## Front Derailleur:

Shimano Dura-Ace R9150 Di2 braze-on

## Rear Derailleur:

Shimano Dura-Ace R9150 Di2 11-speed short cage

## Crankset:

Shimano Dura-Ace R9100, 52/36T, 48cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

CeramicSpeed BB30 Outboard with 24mm bearings

## Chain:

Shimano Dura-Ace 11-speed

## Freewheel / Cassette:

Shimano Dura-Ace 11-speed, 11-28T

## Brake Levers:

Shimano Dura-Ace R9150

## Brake (Front):

eecycleworks regular eebrake with Zipp brake pads for carbon rims

## Brake (Rear):

eecycleworks DM eebrake with Zipp brake pads for carbon rims

## Saddle:

Fizik Arione 00

## Seatpost:

Felt Vibration Reducing Aero Road flip position UHC Advanced + TeXtreme carbon fiber with 3T DiffLock Comfort Module internals, 48 - 51cm: 280mm length, 5mm offset, Felt VariMount Aero Road flip position UHC Advanced + TeXtreme carbon fiber, 54 - 61cm: 350mm length, 25mm offset

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Rims / Wheelset:

Zipp 404 NSW carbon

## Front Hub:

Zipp Cognition, 100mm QR

## Rear Hub:

Zipp Cognition, 11-speed, 130mm QR

## Spokes:

CX-Ray - Black

## Tires:

Continental Grand Prix 4000 S II folding, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector, valve extenders, aero seatpost slot covers, Di2 battery charger



## AR2

## Frame:

Felt Aero Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, BB30 bottom bracket shell and carbon fiber dropouts, 7075 CNC aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing

## Fork:

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), No. 382/DJ, 1.125" - 1.25"

## Stem:

Devox, -7° rise, Ø31.8mm, 48cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Carbon Aero, 80mm reach, 125mm drop, Ø31.8mm, 48 - 54cm: 400mm, 56 - 61cm: 420mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Ultegra R8050 Di2 11-speed

## Front Derailleur:

Shimano Ultegra R8050 Di2 braze-on

## Rear Derailleur:

Shimano Ultegra R8050 Di2 11-speed short cage

## Crankset:

Shimano Ultegra R8000, 52/36T, 48cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Token BB30 with 24mm bearings

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-28T

## Brake Levers:

Shimano Ultegra R8050

## Brake (Front):

Shimano Ultegra R8000 dual pivot caliper with brake pads for carbon rims

## Brake (Rear):

Shimano Ultegra R8000 direct mount caliper with brake pads for carbon rims

## Saddle:

Fizik Arione R3

## Seatpost:

Felt Vibration Reducing Aero Road flip position UHC Advanced + TeXtreme carbon fiber with 3T DiffLock Comfort Module internals, 48 - 51cm: 280mm length, 5mm offset, Felt VariMount Aero Road flip position UHC Advanced + TeXtreme carbon fiber, 54 - 61cm: 350mm length, 25mm offset

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Rims / Wheelset:

DT Swiss ARC1400 Dicut 62 carbon, tubeless ready, 17mm inner width, 62.5mm depth; 1650g (wheel-set)

## Front Hub:

DT Swiss 240 Spline, 100mm QR

## Rear Hub:

DT Swiss 240 Spline, 11-speed, 130mm QR

## Spokes:

DT Swiss Aerocomp 2.0/1.25/2.3 Bladed

## Tires:

Continental Grand Prix 4000 S II folding, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector, valve extenders, aero seatpost slot covers, Di2 battery charger



## AR3

## Frame:

Felt Aero Road UHC Performance carbon fiber, MMC with InsideOut construction, BSA threaded bottom bracket shell, carbon fiber dropouts, replaceable rear derailleur hanger, internal mechanical or internal electronic cable routing

## Fork:

Felt Aero Road UHC Advanced carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), No. 382/DJ, 1.125"" - 1.25""

## Stem:

Devox, -7° rise, Ø31.8mm, 48cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Carbon Aero, 80mm reach, 125mm drop, Ø31.8mm, 48 - 54cm: 400mm, 56 - 61cm: 420mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Ultegra R8000 11-speed

## Front Derailleur:

Shimano Ultegra R8000 braze-on

## Rear Derailleur:

Shimano Ultegra R8000 11-speed short cage

## Crankset:

Shimano Ultegra R8000, 52/36T, 48cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Shimano Hollowtech BSA threaded

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-28T

## Brake Levers:

Shimano Ultegra R8000

## Brake (Front):

Shimano Ultegra R8000 dual pivot caliper with brake pads for carbon rims

## Brake (Rear):

Shimano Ultegra R8000 direct mount caliper with brake pads for carbon rims

## Saddle:

Fizik Arione R5

## Seatpost:

Felt Vibration Reducing Aero Road flip position UHC Advanced carbon fiber with 3T DiffLock Comfort Module internals, 48 - 51cm: 280mm length, 5mm offset, Felt VariMount Aero Road flip position UHC Advanced carbon fiber, 54 - 61cm: 350mm length, 25mm offset

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Rims / Wheelset:

Devox 50 carbon, 17.6mm inner width, 50mm depth

## Front Hub:

Devox ARH1, sealed cartridge bearing, 100mm QR, 20H

## Rear Hub:

Devox ARH1, sealed cartridge bearing, 11-speed, 130mm QR, 24H

## Spokes:

2.0mm stainless steel with aluminum nipples

## Tires:

Continental Grand Prix 4000 S II folding, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector, valve extenders, aero seatpost slot covers



## AR5

## Frame:

Felt Aero Road UHC Performance carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, carbon fiber dropouts, replaceable rear derailleur hanger, internal mechanical or internal electronic cable routing

## Fork:

Felt Aero Road UHC Advanced carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube with integrated crown race, crown, blades and dropouts

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), No. 382/DJ, 1.125"" - 1.25""

## Stem:

Devox, ±7° rise, Ø31.8mm, 48cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Aero Road VariableShape, 80mm reach, 130mm drop, Ø31.8mm, 48 - 54cm: 400mm, 56 - 61cm: 420mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano 105 R7000 11-speed

## Front Derailleur:

Shimano 105 R7000 braze-on

## Rear Derailleur:

Shimano 105 R7000 11-speed short cage

## Crankset:

Shimano 105 R7000, 52/36T, 48cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Shimano Hollowtech BSA threaded

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-28T

## Brake Levers:

Shimano 105 R7000

## Brake (Front):

Shimano 105 R7000 dual pivot caliper

## Brake (Rear):

Shimano 105 R7000 direct mount caliper

## Saddle:

Fizik Arione R7

## Seatpost:

Felt Vibration Reducing Aero Road flip position UHC Advanced carbon fiber with 3T DiffLock Comfort Module internals, 48 - 51cm: 280mm length, 5mm offset, Felt VariMount Aero Road flip position UHC Advanced carbon fiber, 54 - 61cm: 350mm length, 25mm offset

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Rims / Wheelset:

Devox 30; front: 17mm inner width, 27mm depth, rear: 17mm inner width, 30mm depth

## Front Hub:

Devox ARH2, sealed cartridge bearing, 100mm QR, 24H

## Rear Hub:

Devox ARH2, sealed cartridge bearing, 11-speed, 130mm QR, 28H

## Spokes:

2.0 / 1.5 x 2.3mm butted aero stainless steel with aluminum nipples

## Tires:

Grand Sport Race folding, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector, aero seatpost slot covers

## AR FRD | Ultimate | Frame

## Frame:

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert.

## Fork:

Felt Aero Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown, and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearings MR121 {870E-RS} Upper bearing and MR168 {970E-RS} lower bearing with integrated aero headset spacers and integrated top cover for use with non-integrated stem

## Stem:

AR integrated carbon with internal cable and hose routing -6° rise, Ø31.8mm, 48 - 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Seatpost:

Felt VariMount Aero Road UHC Advanced + TeXtreme carbon fiber with high-frequency vibration reducing insert, integrated battery holder, 350mm length\*, 0/20mm offset

\*Seatpost can be cut to length

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Thru Axles:

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 161 (161L + 9 head = 170 total),  
thread: M12 x 1.0P x 18L, Syntace

## Accessories:

Carbon assembly paste, chain plate protector, aero seatpost slot covers, and headset top cover for use with non-integrated stem, thru axles

## AR | Advanced | Frame

## Frame:

Felt Aero Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, aluminum replaceable rear derailleur hanger, internal electronic-specific cable routing, and high-frequency vibration reducing seat post insert.

## Fork:

Felt Aero Road UHC Advanced + TeXtreme carbon fiber monocoque construction, AeroTaper 1.125" - 1.25" carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearings MR121 {870E-RS} Upper bearing and MR168 {970E-RS} lower bearing with integrated aero headset spacers and integrated top cover for use with non-integrated stem

## Stem:

AR integrated carbon with internal cable and hose routing -6° rise, Ø31.8mm, 48 - 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Seatpost:

Felt VariMount Aero Road UHC Advanced + TeXtreme carbon fiber with high-frequency vibration reducing insert, integrated battery holder, 350mm length\*, 0/20mm offset

\*Seatpost can be cut to length

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Thru Axles:

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 161 (161L + 9 head = 170 total),  
thread: M12 x 1.0P x 18L, Syntace

## Accessories:

Carbon assembly paste, chain plate protector, aero seatpost slot covers, and headset top cover for use with non-integrated stem, thru-axles

**FR FRD | Ultimate | Dura-Ace Di2**
**Frame:**

Felt Race Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

**Fork:**

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

**Headset:**

FSA integrated sealed cartridge bearing with carbon fiber cone spacer, Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

**Stem:**

Pro Components Vibe, -10° rise, Ø31.8mm, 43cm: 80mm, 47 - 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

**Handlebar:**

Pro Components Vibe Carbon handlebar compact carbon fiber, Ø31.8mm, 43 - 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

**Grips:**

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

**Shifters:**

Shimano Dura-Ace Di2 R9170 11-speed

**Front Derailleur:**

Shimano Dura-Ace R9150 Di2 braze-on

**Rear Derailleur:**

Shimano Dura-Ace R9150 Di2 11-speed short cage

**Crankset:**

Shimano Dura-Ace R9100, 52/36T, 43 - 47cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

**Bottom Bracket:**

CeramicSpeed BB386 with 24mm bearings

**Chain:**

Shimano Dura-Ace 11-speed

**Freewheel / Cassette:**

Shimano Dura-Ace 11-speed, 11-28T

**Brake Levers:**

Shimano Dura-Ace R9170, hydraulic

**Brake (Front):**

Shimano Dura-Ace R9170 hydraulic disc, 160mm rotor

**Brake (Rear):**

Shimano Dura-Ace R9170 hydraulic disc, 140mm rotor

**Saddle:**

Prologo Dimension Nack

**Seatpost:**

Pro Components Vibe, 20mm offset, Ø27.2mm x 400mm length

**Seatpost Clamp:**

7075 CNC aluminum, titanium bolt and scandium nut, Ø30.6mm

**Rims / Wheelset:**

Shimano Dura-Ace WH-R9170-C40-TL-R12 Carbon

**Thru Axles:**

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

**Tires:**

Continental Grand Prix 5000 Tubeless, 700 x 25c

**Accessories:**

Carbon assembly paste, chain plate protector, Di2 battery charger



## FR | Advanced | Ultegra Di2

## Frame:

Felt Race Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

## Fork:

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

## Stem:

Devox SL, -7° rise, Ø31.8mm, 43 - 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Carbon Variable Shape, 65mm reach, 125mm drop, Ø31.8mm, 43 - 47cm: 38cm, 51cm: 40cm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Ultegra Di2 R8070 11-speed

## Front Derailleur:

Shimano Ultegra R8050 Di2 braze-on

## Rear Derailleur:

Shimano Ultegra R8050 Di2 11-speed short cage

## Crankset:

Shimano Ultegra R8000, 52/36T, 48cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Token BB386 with 24mm bearings

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-30T

## Brake Levers:

Shimano Ultegra R8070, hydraulic

## Brake (Front):

Shimano BR-R8070 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano BR-R8070 hydraulic disc, 140mm rotor

## Saddle:

Prologo Dimension T4.0

## Seatpost:

Devox UHC Performance carbon fiber with microadjust head, 43 - 51cm: Ø27.2mm x 294mm length, 54 - 61cm: Ø27.2mm x 344mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Reynolds AR41 DB Custom carbon, tubeless ready, 21mm inner width, 58mm depth

## Front Hub:

Reynolds Series 1, straight-pull design, 12 x 100mm thru axle, Center Lock

## Rear Hub:

Reynolds Series 1, straight-pull design, 4 pawl, 24T ratchet, 11-speed, 12 x 142mm thru axle, Center Lock

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

Sapim Sprint double butted

## Tires:

Vittoria Rubino Pro G+ folding, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector, tubeless valve stems, Di2 battery charger

## FR | Advanced | Ultegra

## Frame:

Felt Race Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

## Fork:

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

## Stem:

Devox SL, -7° rise, Ø31.8mm, 43 - 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Carbon Variable Shape, 65mm reach, 125mm drop, Ø31.8mm, 43 - 47cm: 38cm, 51cm: 40cm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Ultegra R8020 11-speed

## Front Derailleur:

Shimano Ultegra R8000 braze-on

## Rear Derailleur:

Shimano Ultegra R8000 11-speed short cage

## Crankset:

Praxis Zayante Carbon, 52/36T X-Rings, 43 - 47cm: 167.5mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Praxis Works M30 386EVO

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-30T

## Brake Levers:

Shimano Ultegra R8020, hydraulic

## Brake (Front):

Shimano BR8070 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano BR8070 hydraulic disc, 140mm rotor

## Saddle:

Prologo Dimension T4.0

## Seatpost:

Devox UHC Performance carbon fiber with microadjust head, 43 - 51cm: Ø27.2mm x 294mm length, 54 - 61cm: Ø27.2mm x 344mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Reynolds AR41 DB Custom carbon, tubeless ready, 21mm inner width, 58mm depth

## Front Hub:

Reynolds Series 1, straight-pull design, 12 x 100mm thru axle, Center Lock

## Rear Hub:

Reynolds Series 1, straight-pull design, 4 pawl, 24T ratchet, 11-speed, 12 x 142mm thru axle, Center Lock

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

Sapim Sprint double butted

## Tires:

Vittoria Rubino Pro G+ folding, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector, tubeless valve stems

FR | Advanced | 105

**Frame:**

Felt Race Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

**Fork:**

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

**Headset:**

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

**Stem:**

Devox, ±6° rise, Ø31.8mm, 43cm: 70mm, 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

**Handlebar:**

Devox Ergonomic Road Design, short 65mm reach, 125mm drop, Ø31.8mm, 43 - 47cm: 380mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

**Grips:**

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

**Shifters:**

Shimano 105 ST-R7020, 11-speed, 43 - 47cm: Shimano 105 ST-R7025 Short-reach

**Front Derailleur:**

Shimano 105 R7000 braze-on

**Rear Derailleur:**

Shimano 105 R7000 11-speed short cage

**Crankset:**

Praxis Works Alba, 52/36T, 43 - 47cm: 165mm 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

**Bottom Bracket:**

Praxis Works M30 386EVO

**Chain:**

KMC X-11 EPT, 11-speed

**Freewheel / Cassette:**

Shimano 11-speed, 11-30T

**Brake Levers:**

Shimano 105 ST-R7025, hydraulic

**Brake (Front):**

Shimano 105 BR-R7070 hydraulic disc, 160mm rotor

**Brake (Rear):**

Shimano 105 BR-R7070 hydraulic disc, 140mm rotor

**Saddle:**

Prologo Dimension

**Seatpost:**

Devox UHC Performance carbon fiber with microadjust head, 43 - 51cm: Ø27.2mm x 294mm length, 54 - 61cm: Ø27.2mm x 344mm length

**Seatpost Clamp:**

Felt single bolt, Ø30.6mm

**Rims / Wheelset:**

Devox Road RSL1.9, tubeless compatible 19mm inner width, 23mm depth

**Front Hub:**

Devox RSL3D, sealed cartridge bearing, 12 x 100mm thru axle, Center Lock, 28H

**Rear Hub:**

Devox RSL3D, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

**Thru Axles:**

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

**Spokes:**

2.0mm stainless steel

**Tires:**

Rubino IV G+ folding, 700 x 25c

**Accessories:**

Carbon assembly paste, chain plate protector



FR | Performance, Rim Brake | Ultegra

Frame:

Felt Race Road UHC Performance carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, carbon fiber dropouts, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

Fork:

Felt Race Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

Stem:

Devox, ±6° rise, Ø31.8mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

Handlebar:

Devox Ergonomic Road Design, short 65mm reach, 125mm drop, Ø31.8mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

Grips:

Felt Gel tape with reflective Felt Bubble-Tech F-Wing bar end plugs

Shifters:

Shimano Ultegra R8000 11-speed

Front Derailleur:

Shimano Ultegra R8000 braze-on

Rear Derailleur:

Shimano Ultegra R8000 11-speed short cage

Crankset:

Praxis Works Alba, CLOVER2TONE 52/36T, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

Bottom Bracket:

Praxis Works M30 386EVO

Chain:

KMC X-11 EPT, 11-speed

Freewheel / Cassette:

Shimano 11-speed, 11-30T

Brake Levers:

Shimano Ultegra R8000

Brake (Front):

Shimano Ultegra R8000 dual pivot caliper

Brake (Rear):

Shimano 105 R7010R direct mount caliper

Saddle:

Prologo Dimension

Seatpost:

Devox SuperLite Road with microadjust head, 43 - 51cm: Ø27.2mm x 294mm length, 54 - 61cm: Ø27.2mm x 344mm length

Seatpost Clamp:

Felt single bolt, Ø30.6mm

Rims / Wheelset:

Devox Road RSL3 tubeless compatible 17mm inner width, 24mm depth

Front Hub:

Devox R3, 100mm QR, 28H

Rear Hub:

Devox R3, sealed cartridge bearing, 11-speed, 130mm QR, 28H

Spokes:

2.0 / 1.8mm butted stainless steel

Tires:

Schwalbe LUGANO K-Guard folding, 700 x 25c

Accessories:

Carbon assembly paste, chain plate protector



## FR | Performance, Rim Brake | 105

## Frame:

Felt Race Road UHC Performance carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, carbon fiber dropouts, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing

## Fork:

Felt Race Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown, blades and dropouts

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

## Stem:

Devox, ±6° rise, Ø31.8mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Ergonomic Road Design, short 65mm reach, 125mm drop, Ø31.8mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt Gel tape with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano 105 R7000 11-speed

## Front Derailleur:

Shimano 105 R7000 braze-on

## Rear Derailleur:

Shimano 105 R7000 11-speed short cage

## Crankset:

Praxis Works Alba, 52/36T, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Praxis Works M30 386EVO

## Chain:

KMC X-11 EPT, 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-30T

## Brake Levers:

Shimano 105 R7000

## Brake (Front):

Shimano 105 R7000 dual pivot caliper

## Brake (Rear):

Shimano 105 R7010R direct mount caliper

## Saddle:

Prologo Dimension

## Seatpost:

Devox Lite Road, Ø27.2mm x 300mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Devox Road RSL3 tubeless compatible 17mm inner width, 24mm depth

## Front Hub:

Devox R3, 100mm QR, 28H

## Rear Hub:

Devox R3, sealed cartridge bearing, 11-speed, 130mm QR, 28H

## Spokes:

2.0mm stainless steel

## Tires:

Schwalbe LUGANO K-Guard, 700 x 25c

## Accessories:

Carbon assembly paste, chain plate protector



## FR | 30

## Frame:

Felt Race Road SuperLite custom butted aluminum, Dynaform smooth welded construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger

## Fork:

Felt Race Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

## Stem:

Devox, ±6° rise, Ø31.8mm, 43cm: 70mm, 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Ergonomic Road Design, short 65mm reach, 125mm drop, Ø31.8mm, 43 - 47cm: 380mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt Gel tape with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano 105 ST-R7020, 11-speed, 43 - 47cm: Shimano 105 ST-R7025 Short-reach

## Front Derailleur:

Shimano 105 R7000 band-type, Ø34.9mm

## Rear Derailleur:

Shimano 105 R7000 11-speed short cage

## Crankset:

Shimano 105 R7000, 52/36T, 43 - 47mm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Shimano 68mm BSA threaded

## Chain:

KMC X-11 EPT, 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-30T

## Brake Levers:

Shimano 105 ST-R7025, hydraulic

## Brake (Front):

Shimano 105 BR-R7070 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano 105 BR-R7070 hydraulic disc, 140mm rotor

## Saddle:

Devox MIG

## Seatpost:

Devox UHC Performance carbon fiber with microadjust head, 43 - 51cm: Ø27.2mm x 294mm length, 54 - 61cm: Ø27.2mm x 344mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Devox Road RSL1.9, tubeless compatible 19mm inner width, 23mm depth

## Front Hub:

Devox RSL3D, sealed cartridge bearing, 12 x 100mm thru axle, Center Lock, 28H

## Rear Hub:

Devox RSL3D, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Schwalbe LUGANO K-Guard, 700 x 25c

## Accessories:

Carbon assembly paste

## FR FRD | Ultimate | Frame

## Frame:

Felt Race Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing, 27.2mm seatpost size

## Fork:

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with carbon fiber cone spacer, Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

## Seatpost Clamp:

7075 CNC aluminum, titanium bolt and scandium nut, Ø30.6mm

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Accessories:

Carbon assembly paste, chain plate protector, FSA headset, seatpost clamp, front and rear thru axles

## FR FRD | Ultimate, Rim Brake | Frame

## Frame:

Felt Race Road UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, carbon fiber dropouts, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing, 27.2mm seatpost size

## Fork:

Felt Race Road UHC Ultimate + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown, blades and dropouts. Integrated compression device

## Headset:

FSA integrated sealed cartridge bearing with carbon fiber cone spacer, Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

## Brake (Rear):

eecycleworks DM eebrake short-arm design

## Seatpost Clamp:

7075 CNC aluminum, titanium bolt and scandium nut, Ø30.6mm

## Accessories:

Carbon assembly paste, chain plate protector, FSA headset, Felt seatpost clamp

## FR | Advanced | Frame

## Frame:

Felt Race Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, flat mount disc brake standard, CNC aluminum replaceable rear derailleur hanger, external mechanical or internal electronic cable routing, 27.2mm seatpost size

## Fork:

Felt Race Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with carbon fiber cone spacer, Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 54cm: No.382, 1.125 - 1.25", 56 - 61cm: No.42, 1.125 - 1.5"

## Seatpost Clamp:

7075 CNC aluminum, titanium bolt and scandium nut, Ø30.6mm

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Accessories:

Carbon assembly paste, chain plate protector, FSA headset, Felt seatpost clamp



## DA | Ultimate | Frame

## Frame:

Felt Defined Aero TT/Tri UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, BB30 bottom bracket shell, horizontal dropouts with integrated dropout adjusters, fully integrated proprietary braking system, internal mechanical or electronic cable routing

## Fork:

Felt Bayonet 4 UHC Ultimate + TeXtreme carbon fiber monocoque construction, carbon fiber brake cover, blades, dropouts and crown with Felt compression device

## Headset:

Felt Bayonet 4 integrated, 19mm sealed cartridge bearing

## Stem:

Felt Bayonet 4 Fixed Position, 90 x 0mm, Ø31.8mm and 70 x 30mm, Ø31.8mm

## Brake (Front):

Felt Aero Brake System with integrated cover

## Brake (Rear):

Felt Aero TT/Tri, integrated

## Seatpost:

Felt DA/B Aero UHC Advanced + TeXtreme carbon fiber, 350mm length

## Seatpost Clamp:

Felt Aero Integrated DA/B



## VR | Advanced | Ultegra Di2

## Frame:

Felt Variable Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

## Fork:

Felt Variable Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 61cm: No.42, 1.125 - 1.5"

## Stem:

Devox SL, -7° rise, Ø31.8mm, 43 - 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Road Endurance, 65mm reach, 125mm drop, Ø31.8mm, 43-47cm: 380mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Ultegra Di2 R8070 11-speed

## Front Derailleur:

Shimano Ultegra R8050 Di2 braze-on

## Rear Derailleur:

Shimano Ultegra R8050 Di2 11-speed long cage

## Crankset:

Shimano Ultegra R8000, 50/34T, 43 - 47cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Token BB386 with 24mm bearings

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-34T

## Brake Levers:

Shimano Ultegra R8070, hydraulic

## Brake (Front):

Shimano R8070 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano R8070 hydraulic disc, 140mm rotor

## Saddle:

Prologo Dimension Space T4.0

## Seatpost:

Devox UHC Performance carbon fiber with microadjust head, 43 - 51cm: Ø27.2mm x 344mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Reynolds AR29 DB Custom carbon, tubeless ready, 21mm inner width, 29mm depth

## Front Hub:

Reynolds Series 1, straight-pull design, 12 x 100mm thru axle, Center Lock

## Rear Hub:

Reynolds Series 1, straight-pull design, 4 pawl, 24T ratchet, 11-speed, 12 x 142mm thru axle, Center Lock

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

Sapim Sprint double butted

## Tires:

Vittoria Rubino Pro G+ folding, 700 x 28c

## Accessories:

Carbon assembly paste, chain plate protector, tubeless valve stems, Di2 battery charger



VR | Advanced | 105

## Frame:

Felt Variable Road UHC Performance carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

## Fork:

Felt Variable Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 61cm: No.42, 1.125 - 1.5"

## Stem:

Devox VariableAngle, ±8°/±16° rise, Ø31.8mm, 43cm: 70mm, 47cm : 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Road Endurance, 65mm reach, 125mm drop, Ø31.8mm, 43-47cm: 380mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano 105 ST-R7020 11-speed, 43 - 47cm: Shimano 105 ST-R7025 Short-reach

## Front Derailleur:

Shimano 105 R7000 braze-on

## Rear Derailleur:

Shimano 105 R7000 11-speed long cage

## Crankset:

Shimano 105 R7000, 50/34T, 43 - 47cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Token BB386 with 24mm bearings

## Chain:

KMC X-11 EPT, 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-34T

## Brake Levers:

Shimano 105 ST-R7020, hydraulic 43 - 47cm: Shimano 105 ST-R7025 Short-reach

## Brake (Front):

Shimano 105 BR-R7070 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano 105 BR-R7070 hydraulic disc, 140mm rotor

## Saddle:

Prologo Dimension Space

## Seatpost:

Devox UHC Performance carbon fiber with microadjust head, Ø27.2mm x 344mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Devox Variable Road VR2.1, tubeless compatible 21mm inner width, 23mm depth

## Front Hub:

Devox RSL3D, sealed cartridge bearing, 12 x 100mm thru axle, Center Lock, 28H

## Rear Hub:

Devox RSL3D, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Vittoria Rubino Pro G+, folding, 700 x 28c

## Accessories:

Carbon assembly paste, chain plate protector



## VR | Performance | Ultegra

## Frame:

Felt Variable Road UHC Performance carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

## Fork:

Felt Variable Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA No.42, 1.125 - 1.5", integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap

## Stem:

Devox SL, -7° rise, Ø31.8mm, 43 - 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Road Endurance, 65mm reach, 125mm drop, Ø31.8mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Ultegra R8020 11-speed

## Front Derailleur:

Shimano Ultegra R8000 braze-on

## Rear Derailleur:

Shimano Ultegra R8000 11-speed long cage

## Crankset:

Shimano Ultegra R8000, 50/34T, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Token BB386 with 24mm bearings

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-34T

## Brake Levers:

Shimano Ultegra R8020, hydraulic

## Brake (Front):

Shimano R8070 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano R8070 hydraulic disc, 140mm rotor

## Saddle:

Prologo Dimension Space T4.0

## Seatpost:

Devox UHC Performance carbon fiber with microadjust head, Ø27.2mm x 344mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Reynolds AR29 DB Custom carbon, tubeless ready, 21mm inner width, 29mm depth

## Front Hub:

Reynolds Series 1, straight-pull design, 12 x 100mm thru axle, Center Lock

## Rear Hub:

Reynolds Series 1, straight-pull design, 4 pawl, 24T ratchet, 11-speed, 12 x 142mm thru axle, Center Lock

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

Sapim Sprint double butted

## Tires:

Vittoria Rubino Pro G+ folding, 700 x 28c

## Accessories:

Carbon assembly paste, chain plate protector, tubeless valve stems



VR | Performance | 105

Frame:

Felt Variable Road UHC Performance carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

Fork:

Felt Variable Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

Headset:

FSA No.42, 1.125 - 1.5", integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap

Stem:

Devox VariableAngle, ±8°/±16° rise, Ø31.8mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

Handlebar:

Devox Road Endurance, 65mm reach, 125mm drop, Ø31.8mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

Shifters:

Shimano 105 ST-R7020 11-speed

Front Derailleur:

Shimano Ultegra R8000 braze-on

Rear Derailleur:

Shimano Ultegra R8000 11-speed long cage

Crankset:

Shimano 105 R7000, 50/34T, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

Bottom Bracket:

Token BB386 with 24mm bearings

Chain:

KMC X-11 EPT, 11-speed

Freewheel / Cassette:

Shimano 11-speed, 11-34T

Brake Levers:

Shimano 105 ST-R7020, hydraulic

Brake (Front):

Shimano 105 BR-R7070 hydraulic disc, 160mm rotor

Brake (Rear):

Shimano 105 BR-R7070 hydraulic disc, 140mm rotor

Saddle:

Prologo Dimension Space

Seatpost:

Devox Lite Road, Ø27.2mm x 330mm length

Seatpost Clamp:

Felt single bolt, Ø30.6mm

Rims / Wheelset:

Devox Variable Road VR2.1, tubeless compatible 21mm inner width, 23mm depth

Front Hub:

Devox RSL3D, sealed cartridge bearing, 12 x 100mm thru axle, Center Lock, 28H

Rear Hub:

Devox RSL3D, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

Spokes:

2.0mm stainless steel

Tires:

Schwalbe DURANO RaceGuard folding, 700 x 28c

Accessories:

Carbon assembly paste, chain plate protector



VR | 40

## Frame:

Felt Variable Road Disc FLite custom butted aluminum, hydroform smooth welded construction, BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

## Fork:

Felt Variable Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA No.42, 1.125 - 1.5", integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap

## Stem:

Devox VariableAngle, ±8°/±16° rise, Ø31.8mm, 43cm: 70mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Road Endurance, 65mm reach, 125mm drop, Ø31.8mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Tiagra 10-speed

## Front Derailleur:

Shimano Tiagra clamp-on, Ø31.8mm

## Rear Derailleur:

Shimano Tiagra 10-speed long cage

## Crankset:

Shimano Tiagra, 50/34T, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Token BB386 with 24mm bearings

## Chain:

KMC X-10 EPT, 10-speed

## Freewheel / Cassette:

Shimano 10-speed, 11-34T

## Brake Levers:

Shimano Tiagra

## Brake (Front):

Tektro MD-C610 dual piston flat mount disc, 160mm rotor

## Brake (Rear):

Tektro MD-C610 dual piston flat mount disc, 160mm rotor

## Saddle:

Devox MIG

## Seatpost:

Devox Lite Road, Ø27.2mm x 330mm length

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Devox Variable Road VR2.1, tubeless compatible 21mm inner width, 23mm depth

## Front Hub:

Devox RSL3D, 12 x 100mm thru axle, Center Lock, 28H

## Rear Hub:

Devox RSL3D, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Schwalbe LUGANO K-Guard, 700 x 28c



## VR | 60

## Frame:

Felt Variable Road Disc FLite custom butted aluminum, hydroform smooth welded construction, BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

## Fork:

Felt Variable Road UHC Advanced carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA No.42, 1.125 - 1.5", integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap

## Stem:

Devox VariableAngle, ±8°/±16° rise, Ø31.8mm, 43cm: 70mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Road Endurance, 65mm reach, 125mm drop, Ø31.8mm, 51cm: 400mm, 54 - 56cm: 420mm, 58 - 61cm: 440mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Claris ST-R2000 8-speed

## Front Derailleur:

Shimano Claris R2000 clamp-on, Ø31.8mm

## Rear Derailleur:

Shimano Claris R2000 8-speed short cage

## Crankset:

Shimano Claris R2000, 50/34T, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Sealed cartridge, BSA threaded, square taper axle, 68 x 103mm

## Pedals:

Road platform pedal

## Chain:

KMC 8-Speed

## Freewheel / Cassette:

8-speed, 12-34T

## Brake Levers:

Shimano Claris R2000

## Brake (Front):

Tektro MD-C550 dual piston flat mount disc, 160mm rotor

## Brake (Rear):

Tektro MD-C550 dual piston flat mount disc, 160mm rotor

## Saddle:

Devox MIG

## Seatpost:

Devox Lite Road, Ø27.2mm x 43 - 51cm: Ø27.2mm x 300mm length, 54 - 61cm: Ø27.2mm x 330mm length

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Devox Variable Road VR21, tubeless compatible 21mm inner width, 23mm depth

## Front Hub:

Devox RSL3D, 12 x 100mm thru axle, Center Lock, 28H

## Rear Hub:

Devox RSL3D, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Schwalbe LUGANO K-Guard, 700 x 28c



VR | Advanced | Frame

Frame:

Felt Variable Road UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, carbon fiber BB386 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing, 27.2mm seatpost size

Fork:

Felt Variable Road UHC Advanced + TeXtreme carbon fiber monocoque construction, size specific ControlTaper carbon fiber steerer tube, integrated crown race, crown and blades. Flat mount disc standard, 12 x 100mm thru axle

Headset:

FSA integrated sealed cartridge bearing with carbon fiber cone spacer, Felt top cap, 43 - 47cm: IS-21, 1.125", 51 - 61cm: No.42, 1.125 - 1.5"

Seatpost Clamp:

Felt single bolt, Ø30.6mm

Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

Accessories:

Carbon assembly paste, chain plate protector, FSA headset, Felt seat clamp, front and rear thru axles

**IA FRD Disc**
**Frame:**

Felt Integrated Aero Tri Disc UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

**Fork:**

Felt Dagger Disc UHC Ultimate + TeXtreme carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

**Headset:**

FSA TH-873-CB integrated, 1.125" 36°/45° sealed ceramic ACB cartridge bearings MR115 [873-CB-2RS], split top race H2145 [No.11AGY-2] with Felt compression device

**Stem:**

Felt Dagger Integrated

**Handlebar:**

Devox Dagger UHC Ultimate + Nano base bar with Devox *f*-Bend carbon fiber 3-position extensions

**Grips:**

Felt VelvetGel tape and dimpled gel pads with Felt bar end plugs

**Shifters:**

Shimano Dura-Ace Di2 R9160 TT/Tri 11-speed

**Front Derailleur:**

Shimano Dura-Ace R9150 Di2 braze-on

**Rear Derailleur:**

Shimano Dura-Ace R9150 Di2 11-speed short cage

**Crankset:**

Shimano Dura-Ace R9100, 52/36T, 48 -51cm: 165mm, 54 -56cm: 170mm, 58cm: 172.5mm

**Bottom Bracket:**

CeramicSpeed BSA threaded

**Chain:**

Shimano Dura-Ace,11-speed

**Freewheel / Cassette:**

Shimano Dura-Ace 11-Speed, 11-28T

**Brake Levers:**

Shimano Dura-Ace BR-R9170 TT/Tri hydraulic

**Brake (Front):**

Shimano BR-R9170 hydraulic disc, 140mm rotor

**Brake (Rear):**

Shimano BR-R9170 hydraulic disc, 140mm rotor

**Saddle:**

ISM PS1.0 Ti

**Seatpost:**

Felt VariMount Aero Tri UHC Advanced carbon fiber, 300mm length

**Seatpost Clamp:**

Felt Internaloc integrated with titanium bolts

**Rims / Wheelset:**

Zipp 454 NSW Disc carbon front, Zipp 858 NSW Disc carbon rear

**Front Hub:**

Zipp Cognition, 12 x 100mm thru axle, Center Lock

**Rear Hub:**

Zipp Cognition, 11-speed, 12 x 142mm thru axle, Center Lock

**Thru Axles:**

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

**Spokes:**

CX-Ray - Black

**Tires:**

Continental Grand Prix 5000 folding, 700 x 25c

**Accessories:**

Carbon assembly paste, aero seatpost slot covers, IA CALpac 2.0, Di2 Internal battery charger, Dagger stem cover with 1/4-turn Garmin Mount, valve extenders, IA BTSpac storage box

## IA | Advanced | Force eTap AXS

## Frame:

Felt Integrated Aero Tri Disc UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

## Fork:

Felt Dagger Disc UHC Advanced carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

## Headset:

FSA integrated, 1.125" 36°/45° sealed ACB cartridge bearings MR122 [873E-RS], split top race H2145 [No.11AGY-2] with Felt compression device

## Stem:

Felt Dagger 31.8 Cold Forged

## Handlebar:

Devox Bayonet 3.1 base bar with Devox Ergomod extensions, Ø31.8mm, 48 - 51cm: 390mm, 54 - 58cm: 420mm

## Grips:

Devox Gel tape and new EVA arm pads with anti-microbial cover

## Shifters:

SRAM eTap Clics (aero extension) and Blips (base bar)

## Front Derailleur:

SRAM Force eTap AXS braze-on

## Rear Derailleur:

SRAM Force eTap AXS 12-speed

## Crankset:

SRAM Force DUB, 48/35T, 48cm: 167.5mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

SRAM DUB BSA threaded

## Chain:

SRAM Force 12-speed

## Freewheel / Cassette:

SRAM XG 1270 12-speed, 10-28T

## Brake Levers:

SRAM S-900 Aero HRD Disc hydraulic

## Brake (Front):

SRAM S-900 Aero HRD Disc, 140mm rotor

## Brake (Rear):

SRAM S-900 Aero HRD Disc, 140mm rotor

## Saddle:

ISM PS1.0

## Seatpost:

Felt VariMount Aero Tri UHC Advanced carbon fiber, 300mm length

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Rims / Wheelset:

Reynolds AR58/62 DB Custom carbon, tubeless ready, 21mm inner width, 58mm depth front, 62mm depth rear

## Front Hub:

Reynolds Series 1, straight-pull design, 12 x 100mm thru axle, Center Lock

## Rear Hub:

Reynolds Series 1, straight-pull design, 4 pawl, 24T ratchet, 11-speed XDR driver, 12 x 142mm thru axle, Center Lock

## Thru Axles:

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

Sapim Sprint bladed

## Tires:

Continental Grand Sport Race folding, 700 x 25c

## Accessories:

Carbon assembly paste, aero seatpost slot covers, IA CALpac 2.0, SRAM eTap PowerPack, IA BTSpac storage box, tubeless valve stems

**IA | Advanced | Ultegra Di2**
**Frame:**

Felt Integrated Aero Tri Disc UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

**Fork:**

Felt Dagger Disc UHC Advanced carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

**Headset:**

FSA integrated, 1.125" 36°/45° sealed ACB cartridge bearings MR122 {873E-RS}, split top race H2145 {No.11AGY-2} with Felt compression device

**Stem:**

Felt Dagger 31.8 Cold Forged

**Handlebar:**

Devox Bayonet 3.1 base bar with Devox Ergomod extensions, Ø31.8mm, 48 - 51cm: 390mm, 54 - 58cm: 420mm

**Grips:**

Devox Gel tape and new EVA arm pads with anti-microbial cover

**Shifters:**

Shimano Dura-Ace Di2 R9160 (aero extension) with right hand SW-R600 secondary shifter (base bar)

**Front Derailleur:**

Shimano Ultegra R8050 Di2 braze-on

**Rear Derailleur:**

Shimano Ultegra R8050 Di2 11-speed short cage

**Crankset:**

Shimano Ultegra R8000, 52/36T, 48 -51cm: 165mm, 54 -56cm: 170mm, 58cm: 172.5mm

**Bottom Bracket:**

Shimano Hollowtech BSA threaded

**Chain:**

Shimano 11-speed

**Freewheel / Cassette:**

Shimano 11-speed, 11-28T

**Brake Levers:**

TRP HD-T910 hydraulic with integrated secondary shift buttons (right lever only)

**Brake (Front):**

TRP HD-T910 hydraulic disc, 140mm rotor

**Brake (Rear):**

TRP HD-T910 hydraulic disc, 140mm rotor

**Saddle:**

ISM PS1.0

**Seatpost:**

Felt VariMount Aero Tri UHC Advanced carbon fiber, 300mm length

**Seatpost Clamp:**

Felt Internaloc integrated with titanium bolts

**Rims / Wheelset:**

Reynolds AR58/62 DB Custom carbon, tubeless ready, 21mm inner width, 58mm depth front, 62mm depth rear

**Front Hub:**

Reynolds Series 1, straight-pull design, 12 x 100mm thru axle, Center Lock

**Rear Hub:**

Reynolds Series 1, straight-pull design, 4 pawl, 24T ratchet, 11-speed XDR driver, 12 x 142mm thru axle, Center Lock

**Thru Axles:**

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

**Spokes:**

Sapim Sprint bladed

**Tires:**

Continental Grand Sport Race folding, 700 x 25c

**Accessories:**

Carbon assembly paste, aero seatpost slot covers, IA CALpac 2.0, Di2 Internal battery charger, IA BTSpac storage box, tubeless valve stems

**IA | Advanced | Ultegra**
**Frame:**

Felt Integrated Aero Tri Disc UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

**Fork:**

Felt Dagger Disc UHC Advanced carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

**Headset:**

FSA integrated, 1.125" 36°/45° sealed ACB cartridge bearings MR122 {873E-RS}, split top race H2145 {No.11AGY-2} with Felt compression device

**Stem:**

Felt Dagger 31.8 Cold Forged

**Handlebar:**

Devox Bayonet 3.1 base bar with Devox Ergomod extensions, Ø31.8mm, 48 - 51cm: 390mm, 54 - 58cm: 420mm

**Grips:**

Devox Gel tape and new EVA arm pads with anti-microbial cover

**Shifters:**

microSHIFT TT 11-speed

**Front Derailleur:**

Shimano Ultegra R8000 braze-on

**Rear Derailleur:**

Shimano Ultegra R8000 11-speed short cage

**Crankset:**

Shimano Ultegra R8000, 52/36T, 48 -51cm: 165mm, 54 -56cm: 170mm, 58cm: 172.5mm

**Bottom Bracket:**

Shimano Hollowtech BSA threaded

**Chain:**

Shimano 11-speed

**Freewheel / Cassette:**

Shimano 11-speed, 11-28T

**Brake Levers:**

TRP HD-T910 hydraulic

**Brake (Front):**

TRP HD-T910 hydraulic disc, 140mm rotor

**Brake (Rear):**

TRP HD-T910 hydraulic disc, 140mm rotor

**Saddle:**

ISM PS1.0

**Seatpost:**

Felt VariMount Aero Tri UHC Advanced carbon fiber, 300mm length

**Seatpost Clamp:**

Felt Internaloc integrated with titanium bolts

**Rims / Wheelset:**

Devox 30A Disc, tubeless ready, 19mm width, 30mm depth

**Front Hub:**

Devox RSL3D, sealed cartridge bearing, 12 x 100mm thru axle, 6-bolt, 28H

**Rear Hub:**

Devox RSL3D, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, 6-bolt, 28H

**Thru Axles:**

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

**Spokes:**

2.0mm stainless steel

**Tires:**

Continental Grand Sport Race folding, 700 x 25c

**Accessories:**

Carbon assembly paste, aero seatpost slot covers, IA CALpac 2.0, IA BTSpac storage box

IA | Advanced, Rim Brake | 105

**Frame:**

Felt Integrated Aero Tri UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, horizontal dropouts with integrated dropout adjusters, aerodynamically optimized for direct mount rear brake, internal mechanical or electronic cable routing

**Fork:**

Felt IA UHC Advanced carbon fiber monocoque construction, 1125" carbon fiber steerer, blades, dropouts, crown; aerodynamically optimized for a conventional brake

**Headset:**

FSA integrated, 1.125" 36°/45° sealed ACB cartridge bearings MR122 [873E-RS], split top race H2145 [No.11AGY-2] with Felt compression device

**Stem:**

IA non-integrated -6° rise, Ø31.8mm, 90mm

**Handlebar:**

Devox Bayonet 3.1 base bar with Devox Ergomod extensions, Ø31.8mm, 48 - 51cm: 390mm, 54 - 58cm: 420mm

**Grips:**

Devox Gel tape and new EVA arm pads with anti-microbial cover

**Shifters:**

microSHIFT TT 11-speed

**Front Derailleur:**

Shimano 105 R7000 braze-on

**Rear Derailleur:**

Shimano 105 R7000 11-speed short cage

**Crankset:**

Shimano 105 R7000, 52/36T, 48 -51cm: 165mm, 54 -56cm: 170mm, 58cm: 172.5mm

**Bottom Bracket:**

Shimano Hollowtech BSA threaded

**Chain:**

Shimano 11-speed

**Freewheel / Cassette:**

Shimano 11-speed, 11-28T

**Brake Levers:**

Aero TT/Tri

**Brake (Front):**

Shimano 105 R7000 dual pivot caliper

**Brake (Rear):**

Shimano 105 R7010R direct mount caliper

**Saddle:**

ISM PS1.1

**Seatpost:**

Felt VariMount Aero Tri UHC Advanced carbon fiber, 300mm length

**Seatpost Clamp:**

Felt Internaloc integrated with titanium bolts

**Rims / Wheelset:**

Devox 30A, tubeless ready, 19mm width, 27mm depth

**Front Hub:**

Devox TTR4, 100mm QR, 24H

**Rear Hub:**

Devox TTR3, sealed cartridge bearing, 11-speed, 130mm QR, 28H

**Spokes:**

2.0mm stainless steel

**Tires:**

Continental Grand Sport Race folding, 700 x 25c

**Accessories:**

Carbon assembly paste, aero seatpost slot covers, IA CALpac 2.0, IA BTSpac storage box

## Frame IA FRD Disc

## Frame:

Felt Integrated Aero Tri Disc UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

## Fork:

Felt Dagger Disc UHC Ultimate + TeXtreme carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

## Headset:

FSA TH-873-CB integrated, 1.125" 36°/45° sealed ceramic ACB cartridge bearings MR115 [873-CB-2RS], split top race H2145 [No.11AGY-2] with Felt compression device

## Stem:

Felt Dagger Integrated

## Handlebar:

Devox Dagger UHC Ultimate + Nano base bar with one set of Devox f-Bend carbon fiber 3-position extensions, and one set of Devox Ergomod Carbon extensions

## Grips:

One set of Dimpled gel pads and one set of EVA arm pads with anti-microbial cover

## Seatpost:

Felt VariMount Aero Tri UHC Advanced carbon fiber, 300mm length

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Thru Axles:

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Accessories:

Carbon assembly paste, aero seatpost slot covers, IA CALpac 2.0, Dagger stem cover with 1/4-turn Garmin Mount, valve extenders, IA BTSpac storage box

## IA | Advanced, System | Frame

## Frame:

Felt Integrated Aero Tri Disc UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, horizontal dropouts, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

## Fork:

Felt Dagger Disc UHC Advanced + TeXtreme carbon fiber monocoque construction, 1.125" carbon fiber steerer, upper cover, blades, dropouts, crown; internal disc-brake routing, flat-mount disc brake standard, 12 x 100mm thru axle

## Headset:

FSA integrated, 1.125" 36°/45° sealed ACB cartridge bearings MR122 {873E-RS}, split top race H2145 {No.11AGY-2} with Felt compression device

## Stem:

Felt Dagger Integrated

## Handlebar:

Devox Dagger UHC Ultimate + Nano base bar with one set of Devox f-Bend 3-position extensions, and one set of Devox Ergomod Carbon extensions

## Grips:

One set of Dimpled gel pads and one set of EVA arm pads with anti-microbial cover

## Seatpost:

Felt VariMount Aero Tri UHC Advanced carbon fiber, 300mm length

## Seatpost Clamp:

Felt Internaloc integrated with titanium bolts

## Thru Axles:

Front: 12 x 100 x 118, thread: M12 x 1.5P x 13L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Accessories:

Carbon assembly paste, aero seatpost slot covers, IA CALpac 2.0, Dagger stem cover with 1/4-turn Garmin Mount, valve extenders, IA BTSpac storage box

B14

## Frame:

Felt Aero TT/Tri UHC Performance carbon fiber, MMC with InsideOut construction, BB30 bottom bracket shell, horizontal dropouts with integrated dropout adjusters, internal mechanical or electronic cable routing

## Fork:

Felt Aero TT/Tri UHC Performance carbon fiber blades and dropouts, 1.125" aluminum steerer tube

## Headset:

FSA IS-21 integrated, 1.125" integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap

## Stem:

Devox Tri, ±17° rise, Ø31.8mm, 47cm (650c) : 60mm, 51cm: 80mm, 54 - 56cm: 90mm, 58cm: 100mm, 61cm: 110mm

## Handlebar:

DEVOX Bayonet 3 base bar with DEVOX f-Bend 3-position extensions, Ø31.8mm, 48 - 51cm: 390mm, 54 - 58cm: 420mm, 61cm: 440mm

## Grips:

Felt VelvetGel tape, Felt Tri Tip grips and dimpled gel pads with Felt bar end plugs

## Shifters:

microSHIFT TT 11-speed

## Front Derailleur:

Shimano Ultegra R8000 braze-on

## Rear Derailleur:

Shimano Ultegra R8000 11-speed short cage

## Crankset:

FSA Omega Compact BB30, 50/34T, 47 (650c) :165mm, 51cm: 167.5mm, 54 - 56cm: 170mm, 58 - 61cm: 172.5mm

## Bottom Bracket:

FSA BB30 with 30mm bearings

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-28T

## Brake Levers:

Aero TT/Tri

## Brake (Front):

Dual pivot caliper

## Brake (Rear):

TRP T822 TT direct mount caliper brake

## Saddle:

Prologo Nago Evo Tri40 T2.0

## Seatpost:

Felt DA/B Aero UHC Advanced carbon fiber, 350mm length

## Seatpost Clamp:

Felt Aero Integrated DA/B

## Rims / Wheelset:

Devox 30A, tubeless compatible, 17mm width, 27mm depth

## Front Hub:

Devox TTR4, 100mm QR, 24H

## Rear Hub:

Devox TTR3, sealed cartridge bearing, 11-speed, 130mm QR, 28H

## Spokes:

2.0mm stainless steel

## Tires:

Vittoria Zaffiro Pro Slick folding, 700 x 23c, 47cm: Vittoria Rubino G+ 650 x 23c

## Accessories:

Carbon assembly paste



## FX | Advanced+ | Force CX1

## Frame:

Felt Cyclocross UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, shoulder friendly top tube, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

## Fork:

Felt Cyclocross UHC Ultimate + TeXtreme carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" carbon fiber steerer tube, integrated crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, No.42, 1.125 - 1.5"

## Stem:

Zipp Service Course SL, ±6° rise, Ø31.8mm, 47cm :80mm, 50 - 53cm: 90mm, 55cm: 100mm, 57cm: 110mm, 60cm: 120mm

## Handlebar:

Zipp SL-70 ERGO, Ø31.8mm, 47 - 50cm: 400mm, 53 - 55cm: 420mm, 57 - 60cm: 440mm

## Grips:

Felt CxGel tape with Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

SRAM Force CX1, 1x11

## Rear Derailleur:

SRAM Force CX1, 11-speed long cage

## Crankset:

Quarq Prime Carbon, XSYNC 40T and 38T, 47cm: 165mm, 50cm: 170mm, 53cm: 172.5mm, 55 - 60cm: 175mm

## Bottom Bracket:

Token BB386 with 30mm bearings

## Chain:

SRAM 11-speed

## Freewheel / Cassette:

SRAM 11-speed, 11-36T

## Brake Levers:

SRAM Force CX1, hydraulic

## Brake (Front):

SRAM Force CX1 hydraulic disc flat mount, 160mm Centerline rotor

## Brake (Rear):

SRAM Force CX1 hydraulic disc flat mount, 140mm Centerline rotor

## Saddle:

Prologo XO TiRox

## Seatpost:

Service Course SL Beyond Black, Ø27.2mm x 330mm length

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Zipp/Devox 30 Course disc clincher, tubeless compatible

## Front Hub:

Devox Road RSL3, sealed cartridge bearing, 12 x 100mm thru axle, Center Lock, 28H

## Rear Hub:

Devox Road RSL3, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Schwalbe X-One All Around MicroSkin TL-Easy, folding, 700 x 33c

## Accessories:

Carbon assembly paste, chain plate protector, extra SRAM 40T chainring

## FX | Advanced+ | GRX 800

## Frame:

Felt Cyclocross UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, shoulder friendly top tube, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

## Fork:

Felt Cyclocross UHC Ultimate + TeXtreme carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" carbon fiber steerer tube, integrated crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap and aluminum bolt, No.42, 1.125 - 1.5"

## Stem:

Devox SL, -7° rise, Ø31.8mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Cross SL, drop: 126, reach: 70mm flare 8-deg, Ø31.8mm, 47 - 50cm: 400mm; 53 - 55cm: 420mm, 57-60cm: 440mm

## Grips:

Felt CxGel tape with Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano GRX810, 1x11

## Rear Derailleur:

Shimano GRX812, 11-speed long cage

## Crankset:

Shimano GRX810, 40T, 47-50cm: 170mm, 53-55cm: 172.5mm, 57 - 60cm: 175mm

## Bottom Bracket:

Token BB386 with 24mm bearings

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-40T

## Brake Levers:

Shimano GRX810, hydraulic

## Brake (Front):

Shimano GRX810 hydraulic disc, flat mount, 140mm rotor

## Brake (Rear):

Shimano GRX810 hydraulic disc, flat mount, 140mm rotor

## Saddle:

Prologo X0 T2.0

## Seatpost:

Devox Lite Road, Ø27.2mm x 300mm length

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Devox Variable Road Cx2.1, tubeless compatible 21mm inner width, 23mm depth

## Front Hub:

Devox RSL3D, sealed cartridge bearing, 12 x 100mm thru axle, Center Lock, 28H

## Rear Hub:

Devox RSL3D, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Schwalbe X-One All Around MicroSkin TL-Easy, folding, 700 x 33c

## Accessories:

Carbon assembly paste, chain plate protector



## FX | Advanced | GRX 600

## Frame:

Felt Cyclocross UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, shoulder friendly top tube, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing

## Fork:

Felt Cyclocross UHC Advanced + TeXtreme carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, carbon fiber blades, flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap and aluminum bolt, No.42, 1.125 - 1.5"

## Stem:

Devox, ±6° rise, Ø31.8mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox cross bend, 86mm reach, 130mm drop, 8° flare, Ø31.8mm, 47 - 50cm: 420mm, 53 - 60cm: 440mm

## Grips:

Felt CxGel tape with Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano GRX600 11-speed

## Front Derailleur:

Shimano GRX810 braze-on, with Ø34.9mm clamp adapter

## Rear Derailleur:

Shimano GRX812, 11-speed long cage

## Crankset:

Shimano GRX600, 46-30T, 47-50cm: 170mm, 53-55cm: 172.5mm, 57 - 60cm: 175mm

## Bottom Bracket:

FSA BB386 with 30mm bearings

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-30T

## Brake Levers:

Shimano GRX600, hydraulic

## Brake (Front):

Shimano GRX400 hydraulic disc, 160mm rotor

## Brake (Rear):

ShimanoGRX400 hydraulic disc, 140mm rotor

## Saddle:

Prologo Nago Evo X10 T2.0

## Seatpost:

Devox Lite Road, Ø27.2mm x 300mm length

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Devox Variable Road Cx2.1, tubeless compatible 21mm inner width, 23mm depth

## Front Hub:

Devox R3 Disc, sealed cartridge bearing, 12 x 100mm thru axle, Center Lock, 24H

## Rear Hub:

Devox R3 Disc, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Schwalbe X-One All Around MicroSkin TL-Easy, folding, 700 x 33c

## Accessories:

Carbon assembly paste, chain plate protector

## FX FRD | Ultimate | Frame

## Frame:

Felt Cyclocross UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, shoulder friendly top tube, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing, 27.2mm seatpost size

## Fork:

Felt Cyclocross UHC Ultimate + TeXtreme carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" carbon fiber steerer tube, integrated crown and blades. Flat mount disc standard, 12 x 100mm thru axle

## Headset:

FSA integrated sealed cartridge bearing with carbon fiber cone spacer, Felt top cap, No.42, 1.125 - 1.5"

## Seatpost Clamp:

7075 CNC aluminum, titanium bolt and scandium nut, Ø31.8mm

## Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total),  
thread: M12 x 1.0P x 19L, Syntace

## Accessories:

Carbon assembly paste, chain plate protector, FSA headset, Felt seat clamp, front and rear thru axles



FX | Advanced+ | Frame

Frame:

Felt Cyclocross UHC Advanced + TeXtreme carbon fiber, MMC with InsideOut construction, BB386 bottom bracket shell, 12 x 142mm Syntace style thru axle, shoulder friendly top tube, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical or electronic cable routing, 27.2mm seatpost size

Fork:

Felt Cyclocross UHC Ultimate + TeXtreme carbon fiber monocoque construction, ControlTaper 1.125"-1.5" carbon fiber steerer tube, integrated crown and blades. Flat mount disc standard, 12 x 100mm thru axle

Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap, No.42, 1.125 - 1.5"

Seatpost Clamp:

Felt single bolt, Ø31.8mm

Thru Axles:

Front: 12 x 100 x 123, thread: M12 x 1.5P x 16L, Maxle; Rear: 12 x 142 x 163 (163L + 7 head = 170 total), thread: M12 x 1.0P x 19L, Syntace

Accessories:

Carbon assembly paste, chain plate protector, FSA headset, Felt seat clamp, front and rear thru axles

**BREED | 20**
**Frame:**

Felt Gravel Race Disc Superlite custom butted aluminum, hydroform smooth welded construction, T47 86 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

**Fork:**

Felt Adventure Gravel UHC Advanced carbon fiber full monocoque construction, ControlTaper 1.125" - 1.5" carbon steerer tube, flat mount disc standard, 12 x 100mm thru axle with fender mounts

**Headset:**

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap and aluminum bolt, No.42, 1.125 - 1.5"

**Stem:**

Devox, -7° rise, Ø31.8mm, 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

**Handlebar:**

Devox Gravel SL, 70mm reach, 126mm drop, 16° flare, Ø31.8mm, 47cm: 400mm, 51cm: 420mm, 54cm: 440mm, 56 - 61cm: 460mm

**Grips:**

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

**Shifters:**

SRAM Force Cx1, 1x11

**Rear Derailleur:**

SRAM Force CX1, 11-speed long cage

**Crankset:**

Praxis Works Zayante Carbon-S 1x DM M30, 40T, 47cm: 165mm, 50cm: 170mm, 53cm: 172.5mm, 55 - 60cm: 175mm

**Bottom Bracket:**

Praxis Works M30 T47 86.5

**Chain:**

SRAM 11-speed

**Freewheel / Cassette:**

SRAM 11-speed, 11-42T

**Brake Levers:**

SRAM Force Cx1, hydraulic

**Brake (Front):**

SRAM Force Cx1 hydraulic disc flat mount with 160mm Centerline rotor

**Brake (Rear):**

SRAM Force Cx1 hydraulic disc flat mount with 160mm Centerline rotor

**Saddle:**

Prologo Dimension NDR T4.0

**Seatpost:**

Devox UHC Performance carbon fiber, Ø27.2mm x 47 - 51cm: Ø27.2mm x 300mm length, 54 - 61cm: Ø27.2mm x 350mm length

**Seatpost Clamp:**

Felt single bolt with integrated rack mounts, Ø31.8mm

**Rims / Wheelset:**

Devox GR2.1 SL, 650b Disc, tubeless compatible 21mm inner width

**Front Hub:**

Devox GR3 Disc, sealed cartridge bearing, 12 x 100mm thru axle, 6-bolt, 24H

**Rear Hub:**

Devox GR3 Disc, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, 6-bolt, 24H

**Thru Axles:**

Front: 12 x 100 x 125, thread: M12 x 1.5P x 17L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

**Spokes:**

2.0mm stainless steel

**Tires:**

Vittoria Terreno Dry, TNT Grey, tubeless ready, 650b x 47c

**Accessories:**

Removable rack/fender eye-bolts, removable chainstay fender mount, removable seat stay fender bridge



## BREED | 30

## Frame:

Felt Gravel Race Disc Superlite custom butted aluminum, hydroform smooth welded construction, T47 86 bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

## Fork:

Felt Adventure Gravel UHC Advanced carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, flat mount disc standard, 12 x 100mm thru axle with fender mounts

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap and aluminum bolt, No.42, 1.125 - 1.5"

## Stem:

Devox, ±6° rise, Ø31.8mm, 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox Gravel SL, 70mm reach, 126mm drop, 16° flare, Ø31.8mm, 47cm: 400mm, 51cm: 420mm, 54cm: 440mm, 56 - 61cm: 460mm

## Grips:

Felt CxGel tape with Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano GRX600 11-speed

## Rear Derailleur:

Shimano GRX812, 11-speed long cage

## Crankset:

Shimano GRX600 1x 40T, 47-51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Token T47 86.5

## Chain:

KMC X-11, 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-42T

## Brake Levers:

Shimano GRX600, hydraulic

## Brake (Front):

Shimano BR-RX400 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano BR-RX400 hydraulic disc, 140mm rotor

## Saddle:

Prologo Dimension NDR T4.0

## Seatpost:

Devox UHC Performance carbon fiber, Ø27.2mm x 47 - 51cm: Ø27.2mm x 300mm length, 54 - 61cm: Ø27.2mm x 350mm length

## Seatpost Clamp:

Felt single bolt with integrated rack mounts, Ø31.8mm

## Rims / Wheelset:

Devox GR2.1, 650b Disc, tubeless compatible, 21mm inner width, 23mm depth

## Front Hub:

Devox GR2 Disc, sealed cartridge bearing, 12 x 100mm thru axle, Center Lock, 24H

## Rear Hub:

Devox GR2 Disc, sealed cartridge bearing, 11-speed, 12 x 142mm thru axle, Center Lock, 24H

## Thru Axles:

Front: 12 x 100 x 125, thread: M12 x 1.5P x 17L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Vittoria Terreno Dry, Folding Tan, tubeless ready, 650b x 47c

## Accessories:

Removable rack/fender eye-bolts, removable chainstay fender mount, removable seat stay fender bridge



## BROAM | 30

## Frame:

Felt Adventure Road Disc Superlite custom butted aluminum, smooth welded construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

## Fork:

Felt Adventure Gravel UHC Advanced carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, flat mount disc standard, 12 x 100mm thru axle with mid-mount rack and fender mounts

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap and aluminum bolt, No.42, 1.125 - 1.5"

## Stem:

Devox VariableAngle, ±8°/±16° rise, Ø31.8mm, 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox adventure bend, 86mm reach, 130mm drop, 8° flare, Ø31.8mm, 47cm: 400mm, 51cm: 420mm, 54cm: 440mm, 56 - 61cm: 460mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano GRX600 11-speed

## Front Derailleur:

Shimano GRX810 braze-on, with Ø31.8mm clamp adapter

## Rear Derailleur:

Shimano GRX812, 11-speed long cage

## Crankset:

Shimano GRX600 11 speed, 46/30T, 47-51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Shimano Hollowtech BSA threaded

## Chain:

Shimano 11-speed

## Freewheel / Cassette:

Shimano 11-speed, 11-34T

## Brake Levers:

Shimano GRX600, hydraulic

## Brake (Front):

Shimano BR-RX400 hydraulic disc, 160mm rotor

## Brake (Rear):

Shimano BR-RX400 hydraulic disc, 140mm rotor

## Saddle:

SR Essenza Blackstar Gel

## Seatpost:

Devox Lite Road, Ø27.2mm x 330mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Devox Adventure 2.1 Disc, tubeless compatible 21mm inner width, 23mm depth

## Front Hub:

Devox GR.2 Disc, sealed cartridge bearing, 12 x 100mm thru axle, Center Lock, 28H

## Rear Hub:

Devox GR.1 Disc, 11-speed, 12 x 142mm thru axle, Center Lock, 28H

## Thru Axles:

Front: 12 x 100 x 125, thread: M12 x 1.5P x 17L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Maxxis Refuse with Max Shield, tubeless ready, folding, 700 x 40c



## BROAM | 40

## Frame:

Felt Adventure Road Disc Superlite custom butted aluminum, smooth welded construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

## Fork:

Felt Adventure Gravel UHC Advanced carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, flat mount disc standard, 12 x 100mm thru axle with mid-mount rack and fender mounts

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap and aluminum bolt, No.42, 1.125 - 1.5"

## Stem:

Devox VariableAngle, ±8°/±16° rise, Ø31.8mm, 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox adventure bend, 86mm reach, 130mm drop, 8° flare, Ø31.8mm, 47cm: 400mm, 51cm: 420mm, 54cm: 440mm, 56 - 61cm: 460mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Tiagra 10-speed

## Front Derailleur:

Shimano Tiagra clamp-on, Ø31.8mm

## Rear Derailleur:

Shimano Tiagra 10-speed long cage

## Crankset:

Shimano GRX600 10 speed, 46/30T, 47-51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Shimano Hollowtech BSA threaded

## Chain:

KMC X-10, 10-speed

## Freewheel / Cassette:

Shimano 10-speed, 11-34T

## Brake Levers:

Shimano Tiagra

## Brake (Front):

TRP HY/RD hydraulic flat mount disc, 160mm rotor

## Brake (Rear):

TRP HY/RD hydraulic flat mount disc, 140mm rotor

## Saddle:

SR Essenza Blackstar Gel

## Seatpost:

Devox Lite Road, Ø27.2mm x 330mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Devox Adventure 2.1 Disc, tubeless compatible 21mm inner width, 23mm depth

## Front Hub:

Devox GR.1 Disc, 12 x 100mm thru axle, 6-bolt, 28H

## Rear Hub:

Devox GR.1 Disc, 11-speed, 12 x 142mm thru axle, 6-bolt, 28H

## Thru Axles:

Front: 12 x 100 x 125, thread: M12 x 1.5P x 17L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Maxxis Refuse with Silkworm, folding, 700 x 40c



## BROAM | 60

## Frame:

Felt Adventure Road Disc Superlite custom butted aluminum, smooth welded construction, 68mm BSA threaded bottom bracket shell, 12 x 142mm with Syntace style thru axle, flat mount disc brake standard, replaceable rear derailleur hanger, internal mechanical cable routing

## Fork:

Felt Adventure Gravel UHC Advanced carbon fiber monocoque construction, ControlTaper 1.125" - 1.5" aluminum steerer tube, flat mount disc standard, 12 x 100mm thru axle with mid-mount rack and fender mounts

## Headset:

FSA integrated sealed cartridge bearing with Felt VariableHeight Cone Spacers (20mm PC, 4.5mm aluminum), Felt top cap and aluminum bolt, No.42, 1.125 - 1.5"

## Stem:

Devox VariableAngle, ±8°/±16° rise, Ø31.8mm, 47cm: 80mm, 51cm: 90mm, 54 - 56cm: 100mm, 58cm: 110mm, 61cm: 120mm

## Handlebar:

Devox adventure bend, 86mm reach, 130mm drop, 8° flare, Ø31.8mm, 47cm: 400mm, 51cm: 420mm, 54cm: 440mm, 56 - 61cm: 460mm

## Grips:

Felt VelvetGel tape with 3M reflective base with reflective Felt Bubble-Tech F-Wing bar end plugs

## Shifters:

Shimano Claris R2000 8-speed

## Front Derailleur:

Shimano Claris clamp-on, Ø31.8mm

## Rear Derailleur:

Shimano Sora ST-R3000 long cage

## Crankset:

FSA Tempo Adventure, 46/30T, 47cm: 165mm, 51cm: 170mm, 54 - 56cm: 172.5mm, 58 - 61cm: 175mm

## Bottom Bracket:

Sealed cartridge, BSA threaded, square taper axle, 68 x 118mm

## Chain:

KMC 8-speed

## Freewheel / Cassette:

8-speed, 12-34T

## Brake Levers:

Shimano Claris R2000

## Brake (Front):

Tektro MD-C550 dual piston flat mount disc, 160mm rotor

## Brake (Rear):

Tektro MD-C550 dual piston flat mount disc, 160mm rotor

## Saddle:

SR Essenza Blackstar Gel

## Seatpost:

Devox Lite Road, Ø27.2mm x 330mm length

## Seatpost Clamp:

Felt single bolt, Ø30.6mm

## Rims / Wheelset:

Devox 2.1 Disc, tubeless compatible 21mm inner width, 23mm depth

## Front Hub:

Devox GR.1 Disc, 12 x 100mm thru axle, 6-bolt, 28H

## Rear Hub:

Devox GR.1 Disc, 11-speed, 12 x 142mm thru axle, 6-bolt, 28H

## Thru Axles:

Front: 12 x 100 x 125, thread: M12 x 1.5P x 17L, Maxle; Rear: 12 x 142 x 163 (163L + 9 head = 172 total), thread: M12 x 1.0P x 19L, Syntace

## Spokes:

2.0mm ED Black

## Tires:

Maxxis Refuse with Silkworm, 700 x 40c

## Edict FRD | Ultimate | XTR

## Frame:

Felt XC, 100mm travel, FAST suspension, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleuer hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleuer cable routing

## Shock:

FOX DPS Float, dual lockout remote, 190 x 40mm Trunnion

## Fork:

FOX 32 Step-Cast, 100mm travel, dual lockout remote, 15 x 110mm Boost thru axle

## Headset:

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

## Stem:

Race Face Turbine ±6° rise, Ø31.8mm, SM: 60mm, M/L: 70mm, XL: 90mm

## Handlebar:

Race Face Next carbon flat bar, Ø31.8mm, 9° sweep, 720mm wide

## Grips:

Silicone Foam

## Shifters:

Shimano XTR M9100, 1x12

## Rear Derailleur:

Shimano XTR M9100, 12-speed

## Crankset:

Shimano XTR M9120, 34T, SM: 170mm, MD/LG/XL: 175mm

## Chainguide:

Shimano CD800, ISCG

## Bottom Bracket:

Shimano, BSA threaded, 73mm

## Chain:

Shimano XTR 9100, 12-speed

## Freewheel / Cassette:

Shimano XTR M9100, 12-speed, 10-51T

## Brake Levers:

Shimano

## Brake (Front):

Shimano XTR M9100 hydraulic disc, 180mm rotor

## Brake (Rear):

Shimano XTR M9100 hydraulic disc, 160mm rotor

## Saddle:

Prologo Nago X10, Nack carbon rails

## Seatpost:

Race Face Next SL carbon, Ø30.9 x 400mm

## Seatpost Clamp:

Felt single clamp with titanium bolt, Ø34.9mm

## Rims / Wheelset:

DT Swiss XRC1200 wheelset, tubeless ready, 25mm inner width

## Front Hub:

DT, 15 x 110mm Boost thru axle, Center Lock

## Rear Hub:

DT, Shimano Micro Spline, driver, 12 x 148mm Boost thru axle, Center Lock

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

## Tires:

Maxxis Ardent Race, 3C/EXO/TR, tubeless ready, 29 x 2.2"

[Edict | Advanced | XT](#)
**Frame:**

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

**Shock:**

FOX DPS Performance Elite Float, 190 x 40mm Trunnion

**Fork:**

FOX 32 Step-Cast Performance Elite, 100mm travel, lockout remote, 15 x 110mm Boost thru axle

**Headset:**

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

**Stem:**

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM: 60mm, M/L: 70mm, XL: 90mm

**Handlebar:**

Devox carbon flat top, Ø31.8mm, 8mm rise, 9° sweep, 720mm wide

**Grips:**

Silicone Foam

**Shifters:**

Shimano XT M8100, 1x12

**Rear Derailleur:**

Shimano XT M8100, 12-speed

**Crankset:**

Shimano XT, 32T, SM: 170mm, MD/LG/XL: 175mm

**Chainguide:**

GW, ISCG05 top guide

**Bottom Bracket:**

Shimano, BSA threaded, 73mm

**Chain:**

Shimano XT M8100, 12-speed

**Freewheel / Cassette:**

Shimano XT M8100, 12-speed, 10-51T

**Brake Levers:**

Shimano

**Brake (Front):**

Shimano XT M8100 hydraulic disc, 180mm rotor

**Brake (Rear):**

Shimano XT M8100 hydraulic disc, 160mm rotor

**Saddle:**

Prologo Kappa RS, T2.0 rails

**Seatpost:**

Felt carbon post, forged head, 15mm offset, Ø30.9, SM: 350mm, MD/LG/XL: 400mm

**Seatpost Clamp:**

Felt single bolt, Ø34.9mm

**Rims / Wheelset:**

Custom Reynolds TR249 carbon wheelset, tubeless ready, 24mm inner width

**Front Hub:**

Reynolds, 15 x 110mm Boost thru axle, Center Lock

**Rear Hub:**

Reynolds, Shimano Micro Spline, 12 x 148mm Boost thru axle, Center Lock

**Thru Axles:**

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

**Tires:**

Maxxis Ardent Race, EXO/TR, tubeless ready, 29 x 2.2"

[Edict | Advanced | SLX](#)
**Frame:**

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

**Shock:**

FOX DPS Performance Float, 190 x 40mm Trunnion

**Fork:**

FOX 32 Rhythm, 120mm travel, lockout remote, 15 x 110mm Boost thru axle

**Headset:**

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

**Stem:**

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM: 60mm, M/L: 70mm, XL: 90mm

**Handlebar:**

Devox 6061 flat top, Ø31.8mm, 5mm rise, 9° sweep, 720mm wide

**Grips:**

Devox Pauley Grip, lock-on

**Shifters:**

Shimano SLX M7100, 1x12

**Rear Derailleur:**

Shimano SLX M7100, 12-speed

**Crankset:**

Shimano SLX M7100, 32T, SM: 170mm, MD/LG/XL: 175mm

**Chainguide:**

GW, ISCG05 top guide

**Bottom Bracket:**

Shimano, BSA threaded, 73mm

**Chain:**

Shimano SLX M7100, 12-speed

**Freewheel / Cassette:**

Shimano SLX M7100, 12-speed, 10-51T

**Brake Levers:**

Shimano

**Brake (Front):**

Shimano MT500 hydraulic disc, 180mm rotor

**Brake (Rear):**

Shimano MT500 hydraulic disc, 160mm rotor

**Saddle:**

Prologo Kappa RS, T2.0 rails

**Seatpost:**

Felt butted 6061, dual bolt, 15mm offset, Ø30.9, SM: 350mm, MD/LG/XL: 400mm

**Seatpost Clamp:**

Felt single bolt, Ø34.9mm

**Rims / Wheelset:**

Double wall, tubeless compatible, 25mm inner width

**Front Hub:**

15 x 110mm Boost thru axle, Center Lock, 32H

**Rear Hub:**

Shimano MT510, Micro Spline, 12 x 148mm Boost thru axle, Center Lock, 32H

**Thru Axles:**

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

**Spokes:**

2.0/1.8mm double-butted stainless steel

**Tires:**

Maxxis Ardent, EXO/TR, tubeless ready, 29 x 2.25"

**Edict | Advanced | NX Eagle**
**Frame:**

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

**Shock:**

RockShox Deluxe R, 190 x 40mm Trunnion

**Fork:**

RockShox Recon RL, 120mm travel, lockout remote, 15 x 110mm Boost thru axle

**Headset:**

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

**Stem:**

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM: 60mm, M/L: 70mm, XL: 90mm

**Handlebar:**

Devox 6061 flat top, Ø31.8mm, 5mm rise, 9° sweep, 720mm wide

**Grips:**

Devox Pauley Grip, lock-on

**Shifters:**

SRAM NX Eagle, 1x12

**Rear Derailleur:**

SRAM NX Eagle 12-speed

**Crankset:**

SRAM SX Eagle, 32T, SM: 170mm, MD/LG/XL: 175mm

**Chainguide:**

GW, ISCG05 top guide

**Bottom Bracket:**

SRAM DUB, BSA threaded, 73mm

**Chain:**

SRAM SX Eagle, 12-speed

**Freewheel / Cassette:**

SRAM SX Eagle, 12-speed, 11-50

**Brake Levers:**

Shimano

**Brake (Front):**

Shimano MT400 hydraulic disc, 180mm rotor

**Brake (Rear):**

Shimano MT400 hydraulic disc, 160mm rotor

**Saddle:**

Prologo Kappa RS, STN rails

**Seatpost:**

Felt butted 6061, dual bolt, 15mm offset, Ø30.9, SM: 350mm, MD/LG/XL: 400mm

**Seatpost Clamp:**

Felt single bolt, Ø34.9mm

**Rims / Wheelset:**

Double wall, tubeless compatible, 25mm inner width

**Front Hub:**

15 x 110mm Boost thru axle, Center Lock, 32H

**Rear Hub:**

Shimano driver, 12 x 148mm Boost thru axle, Center Lock, 32H

**Thru Axles:**

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

**Spokes:**

2.0mm stainless steel

**Tires:**

Maxxis Ardent, EXO/TR, tubeless ready, 29 x 2.25"

## Edict FRD

### Frame:

Felt XC, 100mm travel, FAST suspension, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleuer hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleuer cable routing

### Shock:

RockShox Deluxe RT Full Sprint remote, Debonair, custom tune, 190 x 40mm

### Fork:

RockShox SID, World Cup Debonair with Charger 2, 100mm travel, OneLoc full sprint, 15 x 110mm Boost thru axle

### Headset:

FSA integrated sealed cartridge bearing, No.42ACB-A, 1.125" - 1.5"

### Stem:

Race Face Turbine ±6° rise, Ø31.8mm, SM: 60mm, M/L: 70mm, XL: 90mm

### Handlebar:

Race Face Next carbon flat bar, Ø31.8mm, 9° sweep, 720mm wide

### Grips:

Silicone Foam

### Shifters:

SRAM XX1 Eagle, 1x12

### Rear Derailleur:

SRAM XX1 Eagle 12-speed

### Crankset:

SRAM XX1 Eagle, 34T, SM: 170mm, MD/LG/XL: 175mm

### Chinguide:

One Up top guide

### Bottom Bracket:

SRAM GXP, BSA threaded, 73mm

### Chain:

SRAM XX1, 12-speed

### Freewheel / Cassette:

SRAM XG1295, 12-speed, 10-50T

### Brake Levers:

SRAM Level Ultimate

### Brake (Front):

SRAM Level Ultimate hydraulic disc, 180mm rotor

### Brake (Rear):

SRAM Level Ultimate hydraulic disc, 160mm rotor

### Saddle:

Prologo Nago X10, Nack carbon rails

### Seatpost:

Race Face Next SL carbon, Ø30.9 x 400mm

### Seatpost Clamp:

Felt single clamp with titanium bolt, Ø34.9mm

### Rims / Wheelset:

DT Swiss XRC1200 wheelset, tubeless ready, 25mm inner width

### Front Hub:

DT, 15 x 110mm Boost thru axle, 6-bolt

### Rear Hub:

DT, XD driver, 12 x 148mm Boost thru axle, 6-bolt

### Thru Axles:

Rear: Felt leverless 12 x 148 x 166L Syntace style, thread: M12 x 1.0

### Tires:

Maxxis Ardent Race, 3C/EXO/TR, tubeless ready, 29 x 2.2"

## Edict FRD | Ultimate | Frame

## Frame:

Felt XC, 100mm travel, FAST suspension, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing, Ø30.9 seat post size

## Shock:

FOX Float DPS, dual lockout remote, 190 x 40mm Trunnion

## Headset:

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

## Seatpost Clamp:

Felt single clamp with titanium bolt, Ø34.9mm

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

## Accessories:

Frameset includes rear shock, headset, seat clamp and rear thru axle

Edict | Advanced | Frame

Frame:

Felt XC, 100mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable routing, Ø30.9 seat post size

Shock:

FOX DPS Performance Elite Float, 190 x 40mm Trunnion

Headset:

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

Seatpost Clamp:

Felt single bolt, Ø34.9mm

Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

Accessories:

Frameset includes rear shock, headset, seat clamp and rear thru axle

Doctrine | Advanced | XT

Frame:

Felt XC, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, low-direct front derailleur mount, replaceable derailleur hanger, flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

Fork:

FOX 32 Step-Cast Performance Elite, 120mm travel, lockout remote, 15 x 110mm Boost thru axle

Headset:

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, XS/SM: 60mm, M/L: 70mm, XL: 90mm

Handlebar:

Devox carbon flat top, Ø31.8mm, 8mm rise, 9° sweep, 720mm wide

Grips:

Silicone Foam

Shifters:

Shimano XT M8100, 1x12

Rear Derailleur:

Shimano XT M8100, 12-speed

Crankset:

Shimano XT, 32T, SM: 170mm, MD/LG/XL: 175mm

Chinguide:

GW S3, low-direct mount

Bottom Bracket:

Shimano, BSA threaded, 73mm

Chain:

Shimano XT M8100, 12-speed

Freewheel / Cassette:

Shimano XT M8100, 12-speed, 10-51T

Brake Levers:

Shimano

Brake (Front):

Shimano XT M8100 hydraulic disc, 180mm rotor

Brake (Rear):

Shimano XT M8100 hydraulic disc, 160mm rotor

Saddle:

Prologo Kappa RS, T2.0 rails

Seatpost:

Devox carbon post, forged head, 15mm offset, Ø27.2, XS/SM: 350mm, MD/LG/XL: 400mm

Seatpost Clamp:

Felt single bolt, Ø31.8mm

Rims / Wheelset:

Custom Reynolds TR249 carbon wheelset, tubeless ready, 24mm inner width

Front Hub:

Reynolds, 15 x 110mm Boost thru axle, Center Lock

Rear Hub:

Reynolds, Shimano Micro Spline, 12 x 148mm Boost thru axle, Center Lock

Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

Tires:

Schwalbe Racing Ray Evo front + Racing Ralph Evo rear, SnakeSkin, folding, tubeless ready, 29 x 2.25"

## Doctrine | Advanced | SLX

## Frame:

Felt XC, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, low-direct front derailleur mount, replaceable derailleur hanger, flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

## Fork:

FOX 32 Rhythm, 120mm travel, lockout remote, 15 x 110mm Boost thru axle

## Headset:

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

## Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, XS/SM: 60mm, M/L: 70mm, XL: 90mm

## Handlebar:

Devox 6061 butted riser, Ø31.8mm, 15mm rise, 9° sweep, 720mm wide

## Grips:

Devox Pauley Grip

## Shifters:

Shimano SLX M7100, 1x12

## Rear Derailleur:

Shimano SLX M7100, 12-speed

## Crankset:

Shimano SLX M7100, 32T, SM: 170mm, MD/LG/XL: 175mm

## Chinguide:

GW S3, low-direct mount

## Bottom Bracket:

Shimano, BSA threaded, 73mm

## Chain:

Shimano SLX M7100, 12-speed

## Freewheel / Cassette:

Shimano SLX M7100, 12-speed, 10-51T

## Brake Levers:

Shimano

## Brake (Front):

Shimano MT500 hydraulic disc, 180mm rotor

## Brake (Rear):

Shimano MT500 hydraulic disc, 160mm rotor

## Saddle:

Prologo Kappa RS, T2.0 rails

## Seatpost:

Devox butted 6061, dual bolt, 15mm offset, Ø27.2, XS/SM: 350mm, MD/LG/XL: 400mm

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Double wall, tubeless compatible, 25mm inner width

## Front Hub:

15 x 110mm Boost thru axle, Center Lock, 32H

## Rear Hub:

Shimano MT510, Micro Spline, 12 x 148mm Boost thru axle, Center Lock, 32H

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

## Tires:

Schwalbe Racing Ray Perf front + Racing Ralph Perf rear, TwinSkin, folding, tubeless ready, 29 x 2.25"

## Doctrine | Performance | NX Eagle

## Frame:

Felt XC, UHC Performance carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, low-direct front derailleur mount, replaceable derailleur hanger, flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing

## Fork:

RockShox Recon RL, 100mm travel, lockout remote, 15 x 110mm Boost thru axle

## Headset:

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

## Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, XS/SM: 60mm, M/L: 70mm, XL: 90mm

## Handlebar:

Devox 6061 butted riser, Ø31.8mm, 15mm rise, 9° sweep, 720mm wide

## Grips:

Devox Pauley Grip

## Shifters:

SRAM NX Eagle, 1x12

## Rear Derailleur:

SRAM NX Eagle 12-speed

## Crankset:

SRAM SX Eagle, 32T, SM: 170mm, MD/LG/XL: 175mm

## Chinguide:

GW S3, low-direct mount

## Bottom Bracket:

SRAM DUB BB92

## Chain:

SRAM SX Eagle, 12-speed

## Freewheel / Cassette:

SRAM SX Eagle, 12-speed, 11-50

## Brake Levers:

Shimano

## Brake (Front):

Shimano MT400 hydraulic disc, 180mm rotor

## Brake (Rear):

Shimano MT400 hydraulic disc, 160mm rotor

## Saddle:

Devox performance

## Seatpost:

Devox butted 6061, dual bolt, 15mm offset, Ø27.2, XS/SM: 350mm, MD/LG/XL: 400mm

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Double wall, tubeless compatible, 25mm inner width

## Front Hub:

15 x 110mm Boost thru axle, Center Lock, 32H

## Rear Hub:

Shimano driver, 12 x 148mm Boost thru axle, Center Lock, 32H

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

## Spokes:

2.0mm stainless steel

## Tires:

Schwalbe Rocket Ron TwinSkin, tubeless ready, 29 x 2.25"

## Doctrine FRD | Ultimate | Frame

## Frame:

Felt XC, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon drop-outs, ControlTaper head tube, low-direct front derailleur mount, replaceable derailleur hanger, 140mm flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing, Ø27.2 seat post size

## Headset:

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

## Seatpost Clamp:

Felt single clamp with titanium bolt, Ø34.9mm

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

## Accessories:

Frameset includes rear shock, headset, seat clamp and rear thru axle

Doctrine | Advanced | Frame

Frame:

Felt XC, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, low-direct front derailleur mount, replaceable derailleur hanger, 140mm flat mount disc mounts, BB92, 12 x 148mm Syntace style thru axle, internal derailleur cable routing, Ø27.2 seat post size

Headset:

FSA integrated sealed cartridge ACB bearing, No. 42, 1.125" - 1.5"

Seatpost Clamp:

Felt single bolt, Ø31.8mm

Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

Accessories:

Frameset includes headset, seat clamp and rear thru axle

## Dispatch 9 / 60

Frame:  
Felt XC, SuperLite aluminum, hydroform, ControlTaper head tube, replaceable derailleuer hanger, IS disc mounts, 73mm threaded BB, 135mm OLD

Fork:  
RockShox 30 Silver TK, 100mm travel, tapered steerer

Headset:  
FSA integrated sealed cartridge ACB bearing, No. 42, 1125" - 1.5"

Stem:  
Devox,  $\pm 7^\circ$  rise, Ø31.8mm with Cr-Mo bolts, XS: 50mm, S/M: 60mm, L/XL: 70mm

Handlebar:  
Devox 6061 riser, Ø31.8mm, 15mm rise, 6° sweep, 720mm wide

Grips:  
Devox Pauley Grip

Shifters:  
SRAM SX Eagle, 1x12

Rear Derailleur:  
SRAM SX Eagle 12-speed

Crankset:  
SRAM SX Eagle, 32T, SM: 170mm, MD/LG/XL: 175mm

Chinguide:  
Primaero seat-tube mounted top guide

Bottom Bracket:  
SRAM Powerspline, BSA threaded, 73mm

Pedals:  
Low-profile nylon platform

Chain:  
SRAM SX Eagle, 12-speed

Freewheel / Cassette:  
SRAM SX Eagle, 12-speed, 11-50

Brake Levers:  
Shimano

Brake (Front):  
Shimano MT201 hydraulic disc, 180mm rotor

Brake (Rear):  
Shimano MT201 hydraulic disc, 160mm rotor

Saddle:  
Devox performance

Seatpost:  
Devox butted 6061, dual bolt, 15mm offset, Ø27.2, XS/SM: 350mm, MD/LG/XL: 400mm

Seatpost Clamp:  
Felt single bolt, Ø31.8mm

Rims / Wheelset:  
Double wall, tubeless compatible, 25mm inner width

Front Hub:  
100mm QR, Center Lock, 32H

Rear Hub:  
135mm QR, Center Lock, 32H

Spokes:  
2.0mm stainless steel

Tires:  
Schwalbe Rocket Ron TwinSkin, tubeless ready, 29 x 2.25"

## Dispatch 9 / 70

## Frame:

Felt XC, F-Lite aluminum, hydroform, replaceable derailleur hanger, IS disc mounts, 73mm threaded BB, 135mm OLD

## Fork:

SR/Suntour XCM-HLO, 100mm travel, preload, hydraulic lockout

## Headset:

FSA semi-integrated, No.10, 1125"

## Stem:

Devox,  $\pm 7^\circ$  rise, Ø31.8mm with Cr-Mo bolts, XS: 50mm, S/M: 60mm, L/XL: 70mm

## Handlebar:

Devox 6061 riser, Ø31.8mm, 15mm rise, 6° sweep, 720mm wide

## Grips:

Devox Pauley Grip

## Shifters:

MicroSHIFT, 1x9

## Rear Derailleur:

MicroSHIFT Advent M6195M, 9-speed w/clutch

## Crankset:

SR Suntour Veron, 32T, XS/SM: 170mm, MD/LG/XL: 175mm

## Chinguide:

Primaero seat-tube mounted top guide

## Bottom Bracket:

Suntour BB, BSA threaded, 73mm

## Pedals:

Low-profile nylon platform

## Chain:

KMC e9S, 9-speed

## Freewheel / Cassette:

MicroSHIFT, 9-speed, 11-42T

## Brake Levers:

Tektro

## Brake (Front):

Tektro M285 hydraulic disc, 180mm rotor

## Brake (Rear):

Tektro M285 hydraulic disc, 160mm rotor

## Saddle:

Devox performance

## Seatpost:

Devox butted 6061, dual bolt, 15mm offset, Ø27.2, XS/SM: 350mm, MD/LG/XL: 400mm

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Double wall, tubeless compatible, 25mm inner width

## Front Hub:

100mm QR, 6-bolt, 32H

## Rear Hub:

135mm QR, 6-bolt, 32H

## Spokes:

2.0mm stainless steel

## Tires:

Schwalbe Smart Sam K-guard, 29 x 2.25"



## Dispatch 9 / 80

## Frame:

Felt XC, F-Lite aluminum, hydroform, replaceable derailleur hanger, IS disc mounts, 73mm threaded BB, 135mm OLD

## Fork:

SR/Suntour XCT-HLO, 100mm travel, preload, hydraulic lockout

## Headset:

Semi-integrated, 1125"

## Stem:

±7° rise, Ø31.8mm with Cr-Mo bolts, XS: 50mm, S/M: 60mm, L/XL: 70mm

## Handlebar:

6061 riser, Ø31.8mm, 20mm rise, 6° sweep, 720mm wide

## Grips:

Devox Pauley Grip

## Shifters:

MicroSHIFT, 1x8

## Rear Derailleur:

MicroSHIFT Advent M619M, 8-speed

## Crankset:

SunRace 32T, XS/SM: 170mm, MD/LG/XL: 175mm

## Chinguide:

Primaero seat-tube mounted top guide

## Bottom Bracket:

BSA threaded, Square taper, 73mm

## Pedals:

Low-profile resin platform

## Chain:

KMC Z8, 8-speed

## Freewheel / Cassette:

MicroSHIFT, 8-speed, 12-42T

## Brake Levers:

Tektro

## Brake (Front):

Tektro M275 hydraulic disc, 180mm rotor

## Brake (Rear):

Tektro M275 hydraulic disc, 160mm rotor

## Saddle:

Velo VL-1775

## Seatpost:

butted 6061, single bolt, 15mm offset, Ø27.2, XS/SM: 350mm, MD/LG/XL: 400mm

## Seatpost Clamp:

single bolt, Ø31.8mm

## Rims / Wheelset:

Double wall, tubeless compatible, 25mm inner width

## Front Hub:

100mm QR, 6-bolt, 32H

## Rear Hub:

135mm QR, 6-bolt, 32H

## Spokes:

2.0mm stainless steel

## Tires:

Kenda Kadre, 29 x 2.1"

Virtue | Advanced | XT

Frame:

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleuer hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleuer cable/brake hose/dropper post routing

Shock:

FOX Factory Float DPX2, with custom tune, 185 x 52.5 Trunnion

Fork:

FOX 36 Float Performance Elite, 140mm travel, 15 x 110mm Boost thru axle

Headset:

FSA sealed cartridge bearings, semi-integrated, No.57, 1.125 - 1.5"

Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM/MD: 45mm, LG/XL: 55mm

Handlebar:

Devox carbon riser, Ø31.8mm, 15mm rise, 9° sweep, 780mm wide

Grips:

Devox Pauley Grip, lock-on

Shifters:

Shimano XT M8100, 1x12

Rear Derailleur:

Shimano XT M8100, 12-speed

Crankset:

Shimano XT, 32T, SM/MD/LG: 170mm, XL: 175mm

Chainguide:

E-thirteen TRS Race SL guide

Bottom Bracket:

Shimano, BSA threaded, 73mm

Chain:

Shimano XT M8100, 12-speed

Freewheel / Cassette:

Shimano XT M8100, 12-speed, 10-51T

Brake Levers:

Shimano

Brake (Front):

Shimano XT M8120 hydraulic disc, 180mm rotor

Brake (Rear):

Shimano XT M8120 hydraulic disc, 180mm rotor

Saddle:

WTB Volt Race, Cr-Mo rails

Seatpost:

KS LEV Integra with South Paw P, Ø30.9mm, SM: 125mm travel, MD: 150mm travel, LG/XL: 175mm travel

Seatpost Clamp:

Felt single bolt, Ø34.9mm

Rims / Wheelset:

Reynolds Custom TR309 carbon wheelset, tubeless ready, 30mm inner width

Front Hub:

Reynolds, 15 x 110mm Boost thru axle, Center Lock

Rear Hub:

Reynolds, Shimano Micro Spline, 12 x 148mm Boost thru axle, Center Lock

Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

Tires:

Maxxis Minion DHF 3C/EXO/TR 27.5 x 2.5" front + Maxxis Minion DHR II 3C/EXO/TR 27.5 x 2.4" rear, tubeless ready

Virtue | Advanced | SLX

**Frame:**

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

**Shock:**

FOX Performance Elite DPX2, with custom tune, 185 x 52.5 Trunnion

**Fork:**

FOX 36 Float Performance, 140mm travel, 15 x 110mm Boost thru axle

**Headset:**

FSA sealed cartridge bearings, semi-integrated, No.57, 1.125 - 1.5"

**Stem:**

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM/MD: 45mm, LG/XL: 55mm

**Handlebar:**

Devox 6061 riser, Ø31.8mm, 15mm rise, 6° sweep, 800mm wide

**Grips:**

Devox Pauley Grip, lock-on

**Shifters:**

Shimano SLX M7100, 1x12

**Rear Derailleur:**

Shimano SLX M7100, 12-speed

**Crankset:**

Shimano SLX M7100, 32T, SM/MD/LG: 170mm, XL: 175mm

**Chainguide:**

E-thirteen TRS guide

**Bottom Bracket:**

Shimano, BSA threaded, 73mm

**Chain:**

Shimano SLX M7100, 12-speed

**Freewheel / Cassette:**

Shimano SLX M7100, 12-speed, 10-51T

**Brake Levers:**

Shimano

**Brake (Front):**

Shimano MT520 hydraulic disc, 180mm rotor

**Brake (Rear):**

Shimano MT520 hydraulic disc, 180mm rotor

**Saddle:**

WTB Volt Race, Cr-Mo rails

**Seatpost:**

KS LEV SI with South Paw P, Ø30.9mm, SM/MD: 125mm travel, LG/XL: 150mm travel

**Seatpost Clamp:**

Felt single bolt, Ø34.9mm

**Rims / Wheelset:**

Double wall, tubeless compatible, 30mm inner width

**Front Hub:**

15 x 110mm Boost thru axle, Center Lock, 32H

**Rear Hub:**

Shimano MT510, Micro Spline, 12 x 148mm Boost thru axle, Center Lock, 32H

**Thru Axles:**

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

**Spokes:**

2.0/1.8mm double-butted stainless steel

**Tires:**

Maxxis Minion DHF EXO/TR 27.5 x 2.5" front + Maxxis Minion DHR II EXO/TR 27.5 x 2.4" rear, tubeless ready

Virtue | Advanced | NX

**Frame:**

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleuer hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleuer cable/brake hose/dropper post routing

**Shock:**

RockShox Deluxe Select R , with custom tune, 185 x 52.5 Trunnion

**Fork:**

RockShox Pike Select, 140mm travel , 15 x 110mm Boost thru axle

**Headset:**

FSA sealed cartridge bearings, semi-integrated, No.57, 1.125 - 1.5"

**Stem:**

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM/MD: 45mm, LG/XL: 55mm

**Handlebar:**

Devox 6061 riser, Ø31.8mm, 15mm rise, 6° sweep, 800mm wide

**Grips:**

Devox Pauley Grip, lock-on

**Shifters:**

SRAM NX Eagle, 1x12

**Rear Derailleur:**

SRAM NX Eagle 12-speed

**Crankset:**

SRAM SX Eagle, 32T, SM/MD/LG: 170mm, XL: 175mm

**Chinguide:**

1X chainguide

**Bottom Bracket:**

SRAM DUB, BSA threaded, 73mm

**Chain:**

SRAM SX Eagle, 12-speed

**Freewheel / Cassette:**

SRAM SX Eagle, 12-speed, 11-50

**Brake Levers:**

Shimano

**Brake (Front):**

Shimano MT420 hydraulic disc, 180mm rotor

**Brake (Rear):**

Shimano MT420 hydraulic disc, 180mm rotor

**Saddle:**

WTB Volt Comp, steel rails

**Seatpost:**

ExaForm 900i by KS with Westie , Ø30.9mm, SM/MD: 125mm travel, LG/XL: 150mm travel

**Seatpost Clamp:**

Felt single bolt, Ø34.9mm

**Rims / Wheelset:**

Double wall, tubeless compatible, 30mm inner width

**Front Hub:**

15 x 110mm Boost thru axle, Center Lock, 32H

**Rear Hub:**

Shimano driver, 12 x 148mm Boost thru axle, Center Lock, 32H

**Thru Axles:**

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

**Spokes:**

2.0/1.8mm double-butted stainless steel

**Tires:**

Maxxis Minion DHF EXO/TR 27.5 x 2.5" front + Maxxis Minion DHR II EXO/TR 27.5 x 2.4" rear, tubeless ready

## Decree FRD

## Frame:

Felt Trail, 140mm travel, FAST suspension, UHC Ultimate + TeXtreme carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

## Shock:

RockShox Super Deluxe RCT, Debonair with custom tune, 205 x 62.5 Trunnion

## Fork:

RockShox Pike RCT3 Debonair with Charger 2, 150mm travel, 15 x 110mm Boost thru axle

## Headset:

FSA sealed cartridge bearings, semi-integrated upper, external cup lower, DX Pro, 1.125 - 1.5"

## Stem:

Race Face Turbine-R, ±6° rise, Ø35mm, SM/MD: 40mm, LG/XL: 50mm

## Handlebar:

Race Face Next R carbon, Ø35mm, 20mm rise, 8° sweep, 800mm wide

## Grips:

Silicone Foam

## Shifters:

SRAM XX1 Eagle, 1x12

## Rear Derailleur:

SRAM XX1 Eagle 12-speed

## Crankset:

SRAM XX1 Eagle, 34T, SM: 170mm, MD/LG/XL: 175mm

## Chainguide:

E-thirteen TRS Race SL guide

## Bottom Bracket:

SRAM GXP, BSA threaded, 73mm

## Chain:

SRAM XX1, 12-speed

## Freewheel / Cassette:

SRAM XG1295, 12-speed, 10-50T

## Brake Levers:

SRAM Guide Ultimate with carbon lever

## Brake (Front):

SRAM Guide Ultimate hydraulic disc, 180mm rotor

## Brake (Rear):

SRAM Guide Ultimate hydraulic disc, 160mm rotor

## Saddle:

WTB SL8 Carbon, carbon rails

## Seatpost:

RockShox Reverb Stealth with 1X remote, Ø30.9mm, SM: 100mm travel, MD/LG: 125mm travel, XL: 150mm travel

## Seatpost Clamp:

Felt single clamp with titanium bolt, Ø34.9mm

## Rims / Wheelset:

Race Face Next-R wheelset, tubeless ready

## Front Hub:

Race Face, 15 x 110mm Boost thru axle, 6-bolt

## Rear Hub:

Race Face, XD driver, 12 x 148mm Boost thru axle, 6-bolt

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166L Syntace style, thread: M12 x 1.0

## Tires:

Maxxis Minion DHF, 3C/EXO/TR, tubeless ready, 27.5 x 2.5"

## Decree 1

## Frame:

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

## Shock:

RockShox Super Deluxe RCT, Debonair with custom tune, 205 x 62.5 Trunnion

## Fork:

RockShox Pike RC Debonair with Charger 2, 150mm travel, 15 x 110mm Boost thru axle

## Headset:

FSA sealed cartridge bearings, semi-integrated upper, external cup lower, DX Pro, 1.125 - 1.5"

## Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM/MD: 60mm, LG/XL: 70mm

## Handlebar:

Devox carbon riser, Ø31.8mm, 15mm rise, 9° sweep, 780mm wide

## Grips:

Devox Pauley Grip, lock-on

## Shifters:

SRAM X01 Eagle, 1x12

## Rear Derailleur:

SRAM X01 Eagle, 12-speed

## Crankset:

SRAM X01 Eagle, 34T, SM: 170mm, MD/LG/XL: 175mm

## Chainguide:

E-thirteen TRS Race SL guide

## Bottom Bracket:

SRAM GXP, BSA threaded, 73mm

## Chain:

SRAM X01, 12-speed

## Freewheel / Cassette:

SRAM XG1295, 12-speed, 10-50T

## Brake Levers:

SRAM Guide RSC

## Brake (Front):

SRAM Guide RSC hydraulic disc, 180mm rotor

## Brake (Rear):

SRAM Guide RSC hydraulic disc, 160mm rotor

## Saddle:

WTB Volt Race, Cr-Mo rails

## Seatpost:

RockShox Reverb Stealth with 1X remote, Ø30.9mm, SM: 100mm travel, MD/LG: 125mm travel, XL: 150mm travel

## Seatpost Clamp:

Felt single bolt, Ø34.9mm

## Rims / Wheelset:

Race Face Aeffect-R wheelset, tubeless ready

## Front Hub:

Race Face, 15 x 110mm Boost thru axle, 6-bolt

## Rear Hub:

Race Face, XD driver, 12 x 148mm Boost thru axle, 6-bolt

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166L Syntace style, thread: M12 x 1.0

## Tires:

Maxxis Minion DHF, 3C/EXO/TR, tubeless ready, 27.5 x 2.5"

Decree 3

Frame:

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

Shock:

RockShox Deluxe RT3, Debonair with custom tune, 205 x 62.5mm Trunnion

Fork:

RockShox Revelation RC with Charger, 150mm travel, 15 x 110mm Boost thru axle

Headset:

Sealed cartridge bearings, semi-integrated upper, external cup lower, 1.125 - 1.5"

Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM/MD: 60mm, LG/XL: 70mm

Handlebar:

Devox 6061 riser, Ø31.8mm, 15mm rise, 6° sweep, 800mm wide

Grips:

Devox Pauley Grip, lock-on

Shifters:

SRAM GX Eagle, 1x12

Rear Derailleur:

SRAM GX Eagle 12-speed

Crankset:

SRAM Stylo 6K Powerspline, 34T, SM: 170mm, MD/LG/XL: 175mm

Chainguide:

E-thirteen TRS guide

Bottom Bracket:

SRAM Powerspline, BSA threaded, 73mm

Chain:

SRAM GX, 12-speed

Freewheel / Cassette:

SRAM GX, 12-speed, 10-50T

Brake Levers:

SRAM Guide T

Brake (Front):

SRAM Guide T hydraulic disc, 180mm Centerline rotor

Brake (Rear):

SRAM Guide T hydraulic disc, 180mm Centerline rotor

Saddle:

WTB Volt Race, Cr-Mo rails

Seatpost:

KS LEV SI with South Paw P, Ø30.9mm, SM: 100mm travel, MD/LG: 125mm travel, XL: 150mm travel

Seatpost Clamp:

Felt single bolt, Ø34.9mm

Rims / Wheelset:

Alex MD30, tubeless compatible, 30mm inner width

Front Hub:

15 x 110mm Boost thru axle, 6-bolt, 32H

Rear Hub:

XD driver, 12 x 148mm Boost thru axle, 6-bolt, 32H

Thru Axles:

Rear: Felt leverless 12 x 148 x 166L Syntace style, thread: M12 x 1.0

Spokes:

2.0/1.8mm double-butted stainless steel

Tires:

Maxxis Minion DHF, EXO/TR, tubeless ready, 27.5 x 2.5"

Decree 5

Frame:

Felt Trail, 140mm travel, FAST suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 1X specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

Shock:

RockShox Deluxe R, Debonair with custom tune, 205 x 62.5mm Trunnion

Fork:

RockShox REBA RL with Motion Control, 150mm travel , 15 x 110mm Boost thru axle

Headset:

Sealed cartridge bearings, semi-integrated upper, external cup lower, 1:125 - 1.5"

Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM/MD: 60mm, LG/XL: 70mm

Handlebar:

Devox 6061 riser, Ø31.8mm, 15mm rise, 6° sweep, 800mm wide

Grips:

Devox Pauley Grip, lock-on

Shifters:

SRAM NX Eagle, 1x12

Rear Derailleur:

SRAM NX Eagle 12-speed

Crankset:

SRAM NX Eagle, 34T, SM: 170mm, MD/LG/XL: 175mm

Chinguide:

1X chinguide

Bottom Bracket:

SRAM Powerspline, BSA threaded, 73mm

Chain:

SRAM NX, 12-speed

Freewheel / Cassette:

SRAM NX Eagle, 12-speed, 11-50

Brake Levers:

Shimano

Brake (Front):

Shimano MT201 hydraulic disc, 180mm rotor

Brake (Rear):

Shimano MT201 hydraulic disc, 160mm rotor

Saddle:

WTB Volt Comp, steel rails

Seatpost:

KS eTen i dropper with South Paw P, Ø30.9mm, SM/MD: 100mm travel, LG/XL: 125mm travel

Seatpost Clamp:

Felt single bolt, Ø34.9mm

Rims / Wheelset:

Double wall, tubeless compatible, 29mm inner width

Front Hub:

15 x 110mm Boost thru axle, 6-bolt, 32H

Rear Hub:

Shimano driver, 12 x 148mm Boost thru axle, 6-bolt, 32H

Thru Axles:

Rear: Felt leverless 12 x 148 x 166L Syntace style, thread: M12 x 1.0

Spokes:

2.0/1.8mm double-butted stainless steel

Tires:

Maxxis Minion DHF, EXO/TR, tubeless ready, 27.5 x 2.5"

## Decree 1 Frameset

## Frame:

Felt Trail, UHC Advanced carbon fiber, MMC with InsideOut construction, Full carbon dropouts, 140mm travel, FAST suspension, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber trunnion rocker links, 1x specific, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing, Ø30.9mm seat post size

## Shock:

RockShox Super Deluxe RC3, Debonair with custom tune, 205 x 62.5 Trunnion

## Headset:

FSA sealed cartridge bearings, semi-integrated upper, external cup lower, DX Pro, 1.125 - 1.5"

## Seatpost Clamp:

Felt single bolt, Ø34.9mm

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166L Syntace style, thread: M12 x 1.0

## Accessories:

Frameset includes rear shock, headset, seat clamp and rear thru axle

## Compulsion 1

### Frame:

Felt All Mountain, 165mm travel, Equilink suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

### Shock:

FOX Performance Float X2, 205 x 65mm Trunnion

### Fork:

FOX Performance Elite 36, 170mm travel, 15 x 110mm Boost thru axle

### Headset:

FSA sealed cartridge bearings, semi-integrated, No.57, 1.125 - 1.5"

### Stem:

Race Face Aeffect-R, ±6° rise, Ø35mm, S/M: 40mm, L/XL: 50mm

### Handlebar:

Race Face Atlas, Ø35mm, 35mm rise, 8° sweep, 800mm wide

### Grips:

Devox Pauley Grip, lock-on

### Shifters:

SRAM GX Eagle, 1x12

### Rear Derailleur:

SRAM GX Eagle 12-speed

### Crankset:

Descendant 7K Eagle, 34T, SM: 170mm, MD/LG/XL: 175mm

### Chainguide:

MRP SXg top and bottom guide with direct attach bashguard

### Bottom Bracket:

SRAM GXP, BSA threaded, 73mm

### Chain:

SRAM GX, 12-speed

### Freewheel / Cassette:

SRAM GX, 12-speed, 10-50T

### Brake Levers:

SRAM Guide RS

### Brake (Front):

SRAM Guide RS hydraulic disc, 180mm Centerline rotor

### Brake (Rear):

SRAM Guide RS hydraulic disc, 180mm Centerline rotor

### Saddle:

WTB Volt Race, Cr-Mo rails

### Seatpost:

KS LEV Integra dropper with South Paw, Ø30.9mm, SM: 100mm travel, MD: 125mm travel, LG: 150mm travel, XL: 175mm travel

### Seatpost Clamp:

Felt single bolt, Ø34.9mm

### Rims / Wheelset:

Race Face Aeffect-R wheelset, tubeless ready

### Front Hub:

Race Face, 15 x 110mm Boost thru axle, 6-bolt, 32H

### Rear Hub:

Race Face, XD driver, 12 x 148mm Boost thru axle, 6-bolt, 32H

### Thru Axles:

Rear: Felt leverless 12 x 148 x 166L Syntace style, thread: M12 x 1.0

### Tires:

Maxxis DHF, EXO/TR, tubeless ready, 27.5 x 2.6"

**Compulsion 3**
**Frame:**

Felt All Mountain, 165mm travel, Equilink suspension, UHC Advanced carbon fiber, MMC with InsideOut construction, full carbon dropouts, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber rocker links, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing

**Shock:**

FOX Performance Float DPX2, 205 x 65mm Trunnion

**Fork:**

FOX Performance 36, 170mm travel, 15 x 110mm Boost thru axle

**Headset:**

Sealed cartridge bearings, semi-integrated, No.57, 1.125 - 1.5"

**Stem:**

Devox, ±7° rise, Ø35mm, S/M: 45mm, L/XL: 55mm

**Handlebar:**

Devox 6061, Ø35mm, 15mm rise, 9° sweep, 800mm wide

**Grips:**

Devox Pauley Grip, lock-on

**Shifters:**

SRAM NX Eagle, 1x12

**Rear Derailleur:**

SRAM NX 12-speed

**Crankset:**

SRAM NX Eagle, 34T, SM: 170mm, MD/LG/XL: 175mm

**Chainguide:**

MRP AMg top guide with direct attach bashguard

**Bottom Bracket:**

SRAM Powerspline, BSA threaded, 73mm

**Chain:**

SRAM NX, 12-speed

**Freewheel / Cassette:**

SRAM NX Eagle, 12-speed, 11-50

**Brake Levers:**

Shimano

**Brake (Front):**

Shimano Deore MT-500 hydraulic disc, 180mm rotor

**Brake (Rear):**

Shimano Deore MT-500 hydraulic disc, 180mm rotor

**Saddle:**

WTB Volt Comp, Cr-Mo rails

**Seatpost:**

KS eTen i dropper with South Paw P, Ø30.9mm, SM/MD: 100mm travel, LG/XL: 125mm travel

**Seatpost Clamp:**

Felt single bolt, Ø34.9mm

**Rims / Wheelset:**

Double wall, tubeless compatible, 29mm inner width

**Front Hub:**

15 x 110mm Boost thru axle, 6-bolt, 32H

**Rear Hub:**

Shimano driver, 12 x 148mm Boost thru axle, 6-bolt, 32H

**Thru Axles:**

Rear: Felt leverless 12 x 148 x 166L Syntace style, thread: M12 x 1.0

**Spokes:**

2.0/1.8mm double-butted stainless steel

**Tires:**

Maxxis DHF, EXO/TR, tubeless ready, 27.5 x 2.6"

## Compulsion 1 Frameset

## Frame:

Felt All Mountain, UHC Advanced carbon fiber, MMC with InsideOut construction, Full carbon dropouts, 170mm travel, Equilink suspension, ControlTaper head tube, post disc mount, replaceable derailleur hanger, 73mm threaded BB, carbon fiber trunnion rocker links, 12 x 148mm Syntace style thru axle, internal derailleur cable/brake hose/dropper post routing, Ø30.9mm seat post size

## Shock:

FOX Performance Float X2, 205 x 65mm Trunnion

## Headset:

FSA sealed cartridge bearings, semi-integrated, No.57, 1.125 - 1.5"

## Seatpost Clamp:

Felt single bolt, Ø34.9mm

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166L Syntace style, thread: M12 x 1.0

Frameset includes rear shock, headset, seat clamp and rear thru axle



**DD | 30**
**Frame:**

Felt Fat, SuperLite aluminum, hydroform, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, clamp adaptor for high direct type front derailleur mount

**Fork:**

Felt Fat hydroformed 6061 aluminum, tapered steerer, post-mount disc, rack mounts, 15 x 150mm thru axle

**Headset:**

FSA sealed cartridge bearings, semi-integrated upper, external cup lower, No.57E/62, 1.125 - 1.5"

**Stem:**

Felt, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM: 60mm, MD: 70mm, LG: 80mm

**Handlebar:**

Devox carbon flat top, Ø31.8mm, 8mm rise, 9° sweep, 760mm wide

**Grips:**

Devox Pauley Grip, lock-on

**Shifters:**

Shimano SLX M7000, 1x11

**Rear Derailleur:**

Shimano M7000, 11-speed, Shadow Plus, long cage

**Crankset:**

Race Face Aeffect, 32T, SM: 170mm, MD/LG: 175mm

**Bottom Bracket:**

Race Face, BSA threaded, 100mm

**Pedals:**

Low-profile nylon platform

**Chain:**

Shimano HG60, 11-speed

**Freewheel / Cassette:**

Shimano SLX M7000, 11-speed, 11-46T

**Brake Levers:**

Shimano

**Brake (Front):**

Shimano Deore M6000 hydraulic disc, 180mm rotor

**Brake (Rear):**

Shimano Deore M6000 hydraulic disc, 160mm rotor

**Saddle:**

WTB Volt Race, Cr-mo rails

**Seatpost:**

Felt butted 6061, dual bolt, 15mm offset, Ø30.9. SM: 350mm, MD/LG: 400mm

**Seatpost Clamp:**

Felt single bolt, Ø34.9mm

**Rims / Wheelset:**

Single wall with machined cut outs, tubeless compatible, 80mm inner width

**Front Hub:**

15 x 150mm thru axle, 6-bolt, 32H

**Rear Hub:**

Shimano driver, 12 x 197mm, 6-bolt, 32H

**Thru Axles:**

Front: Felt tool free 15 x 150 x 190, thread: M15 x 1.5P x 11L, Maxle; Rear: Felt tool free 12 x 197 x 218, thread: M12 x 1.0P x 18L, Syntace

**Spokes:**

2.0mm stainless steel

**Tires:**

Schwalbe Jumbo Jim EVO, SnakeSkin, TLE, folding, tubeless ready, 26 x 4.8"

**DD | 70**
**Frame:**

Felt Fat, SuperLite aluminum, hydroform, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, clamp adaptor for high direct type front derailleur mount

**Fork:**

Felt Fat hydroformed 6061 aluminum, tapered steerer, post-mount disc, rack mounts, 15 x 150mm thru axle

**Headset:**

FSA sealed cartridge bearings, semi-integrated upper, external cup lower, No.57E/62, 1.125 - 1.5"

**Stem:**

Felt, ±7° rise, Ø31.8mm with Cr-Mo bolts, SM: 60mm, MD: 70mm, LG: 80mm

**Handlebar:**

Devox 6061 butted flat top, Ø31.8mm, 5mm rise, 9° sweep, 760mm wide

**Grips:**

Devox Pauley Grip

**Shifters:**

SRAM NX, 1x11

**Rear Derailleur:**

SRAM NX Eagle 11-speed, long cage

**Crankset:**

Race Face Aeffect, 32T, SM: 170mm, MD/LG: 175mm

**Bottom Bracket:**

Race Face, BSA threaded, 100mm

**Pedals:**

Low-profile nylon platform

**Chain:**

SRAM PC1110, 11-speed

**Freewheel / Cassette:**

SRAM PG 1130, 11-speed, 11-42T

**Brake Levers:**

Tektro

**Brake (Front):**

Tektro M285 hydraulic disc, 180mm rotor

**Brake (Rear):**

Tektro M285 hydraulic disc, 160mm rotor

**Saddle:**

Devox MTB performance

**Seatpost:**

Felt butted 6061, dual bolt, 15mm offset, Ø30.9. SM: 350mm, MD/LG: 400mm

**Seatpost Clamp:**

Felt single bolt, Ø34.9mm

**Rims / Wheelset:**

Single wall, tubeless compatible, 80mm inner width

**Front Hub:**

15 x 150mm thru axle, 6-bolt, 32H

**Rear Hub:**

Shimano driver, 12 x 197mm, 6-bolt, 32H

**Thru Axles:**

Front: Felt tool free 15 x 150 x 190, thread: M15 x 1.5P x 11L, Maxle; Rear: Felt tool free 12 x 197 x 218, thread: M12 x 1.0P x 18L, Syntace

**Spokes:**

2.0mm stainless steel

**Tires:**

Schwalbe Jumbo Jim EVO, SnakeSkin, TLE, folding, tubeless ready, 26 x 4.8"

Q20

## Frame:

Felt Q Kids Series, Dynaform 6061 aluminum, 1-1/8" head tube, forged dropouts, standard 68mm bottom bracket, 135mm OLD, Ø27.2mm seatpost, Ø31.8mm front derailleur clamp

## Fork:

SR Suntour M3010, 40mm travel

## Headset:

FSA Threadless 1-1/8"

## Stem:

Felt, ±10° rise, Ø31.8mm with Cr-Mo bolts, 50mm

## Handlebar:

Felt MTB Kids aluminum, Ø31.8mm, 15mm rise x 9° sweep, 600mm wide

## Grips:

Felt Kids MTB w/ end plug

## Shifters:

Shimano Tourney Revo, 1x7

## Rear Derailleur:

Shimano Tourney, 7-speed

## Crankset:

Forged Aluminum with chainring guard, 38T, 140mm

## Bottom Bracket:

Sealed cartridge, BSA threaded, square taper axle, 68mm

## Pedals:

Kids nylon platform

## Chain:

Sunrace M54, 7-speed

## Freewheel / Cassette:

Sunrace 7-speed freewheel, 13-34T

## Brake Levers:

Tektro

## Brake (Front):

Tektro 855AL, V-type

## Brake (Rear):

Tektro 855AL, V-type

## Saddle:

Felt Kid's performance

## Seatpost:

Felt 6061, single bolt, 15mm offset, Ø27.2, 250mm

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Aluminum single wall, 25mm inside, V-brake

## Front Hub:

Aluminum, 100mm bolt-on, 32H

## Rear Hub:

Thread-on type, aluminum, 135mm bolt-on, 32H

## Spokes:

2.0mm stainless steel

## Tires:

Impac Ridgepac, 20 x 2.0"

Q24

## Frame:

Felt Q Kids Series, Dynaform 6061 aluminum, 1-1/8" head tube, forged dropouts, standard 68mm bottom bracket, 135mm OLD, Ø27.2mm seatpost, Ø31.8mm front derailleur clamp

## Fork:

SR Suntour XCT JR, 50mm travel

## Headset:

FSA Threadless 1-1/8"

## Stem:

Felt, ±10° rise, Ø31.8mm with Cr-Mo bolts, 50mm

## Handlebar:

Felt MTB Kids aluminum, Ø31.8mm, 15mm rise x 9° sweep, 600mm wide

## Grips:

Felt Kids MTB w/ end plug

## Shifters:

Shimano Tourney Revo, 1x8

## Rear Derailleur:

Shimano Tourney TX, 8-speed

## Crankset:

Forged Aluminum with chainring guard, 34T, 155mm

## Bottom Bracket:

Sealed cartridge, BSA threaded, square taper axle, 68mm

## Pedals:

Kids nylon platform

## Chain:

Sunrace M84, 8-speed

## Freewheel / Cassette:

Sunrace 8-speed freewheel, 13-34T

## Brake Levers:

Tektro

## Brake (Front):

Tektro 855AL, V-type

## Brake (Rear):

Tektro 855AL, V-type

## Saddle:

Felt Kid's performance

## Seatpost:

Felt 6061, single bolt, 15mm offset, Ø27.2, 300mm

## Seatpost Clamp:

Felt single bolt, Ø31.8mm

## Rims / Wheelset:

Aluminum single wall, 25mm inside, V-brake

## Front Hub:

Aluminum, 100mm QR, 32H

## Rear Hub:

Thread-on type, aluminum, 135mm bolt-on, 32H

## Spokes:

2.0mm stainless steel

## Tires:

Impac Ridgepac, 24 x 2.1"

Q24 Disc

Frame:

Felt Q Kids Series, Dynaform 6061 aluminum, 1-1/8" head tube, forged dropouts, IS disc mounts, standard 68mm bottom bracket, 135mm OLD, Ø27.2mm seatpost, Ø31.8mm front derailleur clamp

Fork:

SR Suntour XCT JR, 50mm travel

Headset:

FSA Threadless 1-1/8"

Stem:

Felt, ±10° rise, Ø31.8mm with Cr-Mo bolts, 50mm

Handlebar:

Felt MTB Kids aluminum, Ø31.8mm, 15mm rise x 9° sweep, 600mm wide

Grips:

Felt Kids MTB w/ end plug

Shifters:

SRAM X5, 1x9

Rear Derailleur:

SRAM X5, 9-speed

Crankset:

SRAM NX Powerspline, 28T, 155mm

Bottom Bracket:

SRAM Powerspline, BSA threaded, 68mm

Pedals:

Kids nylon platform

Chain:

KMC Z99, 9-speed

Freewheel / Cassette:

Sunrace 9-speed freewheel, 11-36T

Brake Levers:

Tektro

Brake (Front):

Tektro M285 hydraulic disc, 160mm rotor

Brake (Rear):

Tektro M285 hydraulic disc, 160mm rotor

Saddle:

Felt Kid's performance

Seatpost:

Felt 6061, single bolt, 15mm offset, Ø27.2, 300mm

Seatpost Clamp:

Felt single bolt, Ø31.8mm

Rims / Wheelset:

Aluminum double wall, 25mm inside, Disc

Front Hub:

Aluminum, 100mm QR, 6-bolt, 32H

Rear Hub:

Thread-on type, aluminum, 135mm QR, 6-bolt, 32H

Spokes:

2.0mm stainless steel

Tires:

Schwalbe Smart Sam, 24 x 2.35"

## Redemption | 30

## Frame:

Felt All Mountain, 150mm travel, Shimano e-Bike specific, double-butted 6061 aluminum, fully integrated down tube, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, 12 x 148mm Syntace style thru axle

## Shock:

Rock Shox Deluxe RT, Debonair, 185 x 52.5mm Trunnion

## Fork:

Rock Shox Yari RC Debonair, 150mm travel, 15 x 110mm Boost, E-Bike specific

## Headset:

FSA sealed cartridge bearings, semi-integrated, No.57, 1.125 - 1.5"

## Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, 35mm length

## Handlebar:

Devox E-MTB 6061 butted riser, Ø31.8mm, 25mm rise, 9° sweep, 780mm wide, custom internal wire routing

## Grips:

Devox Pauley Grip, lock-on

## Shifters:

Shimano SLX M7000, 1x11

## Rear Derailleur:

Shimano XT, 11-speed, Shadow Plus, long cage

## Crankset:

Shimano E8000, 34T, SM/MD 165mm, LG/XL: 170mm

## Chainguide:

MRP E-Guide

## Bottom Bracket:

Shimano e8000 MTB drive, 250W output, 25 km/h

## Battery:

Shimano E8020, 500Wh integrated

## Chain:

KMC X11-E, 11-speed

## Freewheel / Cassette:

Shimano SLX, 11-speed, 11-46T

## Brake Levers:

Shimano

## Brake (Front):

Shimano MT520 4 piston hydraulic disc, 203mm rotor

## Brake (Rear):

Shimano MT520 4 piston hydraulic disc, 180mm rotor

## Saddle:

WTB Silverado, Cr-Mo rails

## Seatpost:

KS LEV Integra dropper with South Paw, Ø30.9mm, SM/MD: 100mm travel, LG: 125mm travel, XL: 150mm travel

## Seatpost Clamp:

Felt single bolt, Ø34.9mm

## Rims / Wheelset:

WTB Scraper i35, tubeless compatible, 35mm inner width

## Front Hub:

Shimano Deore, 15 x 110mm Boost thru axle, Center lock, 32H

## Rear Hub:

Shimano Deore, 12 x 148mm Boost thru axle, Center Lock, 32H

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

## Spokes:

2.0mm butted stainless steel

## Tires:

Maxxis Minion DHF front, Maxxis High Roller 2 rear, 3C/EXO, tubeless ready, 27.5 x 2.8"

## Accessories:

Battery charger

## Redemption | 50

## Frame:

Felt All Mountain, 150mm travel, Shimano e-Bike specific, double-butted 6061 aluminum, fully integrated down tube, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, 12 x 148mm Syntace style thru axle

## Shock:

Rock Shox Deluxe R, Debonair, 185 x 52.5mm Trunnion

## Fork:

Rock Shox Sektor Debonair, 150mm travel, 15 x 110mm Boost, E-Bike specific

## Headset:

FSA sealed cartridge bearings, semi-integrated, No.57, 1.125 - 1.5"

## Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, 35mm length

## Handlebar:

Devox E-MTB 6061 butted riser, Ø31.8mm, 25mm rise, 9° sweep, 780mm wide, custom internal wire routing

## Grips:

Devox Pauley Grip, lock-on

## Shifters:

Shimano Deore M6000, 1x10

## Rear Derailleur:

Shimano Deore, 10-speed, Shadow Plus, long cage

## Crankset:

Shimano E8000, 34T, SM/MD 165mm, LG/XL: 170mm

## Chainguide:

MRP E-Guide

## Bottom Bracket:

Shimano E7000 MTB drive, 250W output, 25 km/h

## Battery:

Shimano E8020, 500Wh integrated

## Chain:

KMC X10-E, 10-speed

## Freewheel / Cassette:

Shimano, 10-speed, 11-42T

## Brake Levers:

Shimano

## Brake (Front):

Shimano MT500 hydraulic disc, 203mm rotor

## Brake (Rear):

Shimano MT500 hydraulic disc, 180mm rotor

## Saddle:

Devox MTB

## Seatpost:

KS eTen i dropper with Westie, Ø30.9mm,  
SM/MD: 100mm travel, LG/XL: 125mm travel

## Seatpost Clamp:

Felt single bolt, Ø34.9mm

## Rims / Wheelset:

E-Double wall, tubeless compatible, 35mm inner width

## Front Hub:

Shimano MT400, 15 x 110mm Boost thru axle, Center lock, 32H

## Rear Hub:

Shimano MT400, 12 x 148mm Boost thru axle, Center Lock, 32H

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

## Spokes:

2.0mm butted stainless steel

## Tires:

Maxxis Minion DHF front, Maxxis High Roller 2 rear, Dual, tubeless ready, 27.5 x 2.8"

## Accessories:

Battery charger

## Surplus | 50

## Frame:

Felt 27.5+, Shimano e-bike design, 6061 aluminum, fully integrated down tube, ControlTaper integrated head tube, post disc mount, replaceable derailleur hanger, 12 x 148mm Syntace style thru axle

## Fork:

RockShox Recon RL Solo Air, 130mm travel, 15 x 110mm Boost, E-Bike specific

## Headset:

FSA sealed cartridge bearings, semi-integrated, No.57, 1125 - 1.5"

## Stem:

Devox, ±7° rise, Ø31.8mm with Cr-Mo bolts, 35mm length

## Handlebar:

Devox E-MTB 6061 butted riser, Ø31.8mm, 25mm rise, 9° sweep, 780mm wide, custom internal wire routing

## Grips:

Devox Pauley Grip, lock-on

## Shifters:

Shimano Deore M6000, 1x10

## Rear Derailleur:

Shimano Deore, 10-speed, Shadow Plus, long cage

## Crankset:

Shimano E8000, 34T, SM/MD 165mm, LG/XL: 170mm

## Bottom Bracket:

Shimano E7000 MTB drive, 250W output, 25 km/h

## Battery:

Shimano E8020, 500Wh integrated

## Chain:

KMC X10-E, 10-speed

## Freewheel / Cassette:

Shimano, 10-speed, 11-42T

## Brake Levers:

Shimano

## Brake (Front):

Shimano MT400 hydraulic disc, 203mm rotor

## Brake (Rear):

Shimano MT400 hydraulic disc, 180mm rotor

## Saddle:

Devox MTB

## Seatpost:

KS 900 i dropper with Westie, Ø30.9mm, SM/ MD: 100mm travel, LG/XL: 125mm travel

## Seatpost Clamp:

Felt single bolt, Ø34.9mm

## Rims / Wheelset:

E-Double wall, tubeless compatible, 35mm inner width

## Front Hub:

Shimano MT400, 15 x 110mm Boost thru axle, Center lock, 32H

## Rear Hub:

Shimano MT400, 12 x 148mm Boost thru axle, Center Lock, 32H

## Thru Axles:

Rear: Felt leverless 12 x 148 x 166, thread: M12 x 1.0P x 18L, Syntace

## Spokes:

2.0mm butted stainless steel

## Tires:

Maxxis Rekon+, Dual, tubeless ready, 27.5 x 2.8"

## Accessories:

Battery charger

## AR GEOMETRY

Size	48	51	54	56	58	61
HA	71	72.5	73	73.5	74	74
SA	74.5	74	73.5	73.5	73.5	73
TT Horiz	510	530	545	560	580	605
TT C-C	-	-	-	-	-	-
HT Length	110	120	140	160	180	210
Seat Tube C-T	440	470	500	520	550	590
Seat Tube C-C	420	450	480	500	530	570
BB Drop	72	70	70	70	70	70
BB Rise	-	-	-	-	-	-
CS	408	408	410	410	410	410
Front Center	577	579	580	588	603	622
Wheelbase	974	977	980	988	1003	1024
Standover	710	740	764	785	812	845
Fork Length	370	370	370	370	370	370
Rake	52	50	45	43	43	43
Lower HS Stack	1	1	1	1	1	1
Reach	367	379	383	392	406	417
Stack	510	523	546	567	588	617

## FR GEOMETRY

Size	43	47	51	54	56	58	61
HA	70.5	71.5	72.25	73	73.5	73.75	74
SA	75.25	74.5	74	73.5	73.5	73.25	73
TT Horiz	495	512	530	548	563	583	604
TT C-C	-	-	-	-	-	-	-
HT Length	90	100	115	135	155	177	205
Seat Tube C-T	405	425	465	505	525	555	595
Seat Tube C-C	-	-	-	-	-	-	-
BB Drop	72	72	72	70	70	70	70
BB Rise	-	-	-	-	-	-	-
CS	403	403	403	405	405	407	410
Front Center	573	575	577	585	591	606	621
Wheelbase	965	967	969	980	986	1003	1021
Standover	657	676	710	747	767	790	828
Fork Length	380	380	380	380	380	380	380
Rake	52	52	47	47	43	43	43
Lower HS Stack	1	1	1	1	1	1	1
Reach	362	369	377	385	394	405	414
Stack	499	512	530	550	572	594	621

## DA GEOMETRY

Size	51	54	56	58	
HA	72.5	73	73	73	
SA	76-78.1	76-78	76-78	76-78	
TT Horiz	500-520	521-540	541-560	561-580	
TT C-C	520	540	560	580	
HT Length	80	88	108	128	
Seat Tube C-T	510	540	560	580	
Seat Tube C-C	495	525	545	565	
BB Drop	70	70	70	70	
BB Rise	-	-	-	-	
CS	395	395	395	395	
Front Center	577	593	614	635	
Wheelbase	962	978	999	1020	
Standover	770	794	813	833	
Fork Length	370	370	370	370	
Rake	40	40	40	40	
Lower HS Stack	1	1	1	1	
Reach	399	416	432	447	
Stack	488	497	516	536	

## VR GEOMETRY

Size	43	47	51	54	56	58	61
HA	70.5	71.5	72.25	73	73.5	73.75	74
SA	75.25	74.5	74	73.5	73.5	73.25	73
TT Horiz	495	512	530	548	563	583	604
TT C-C	-	-	-	-	-	-	-
HT Length	90	100	115	135	155	177	205
Seat Tube C-T	405	425	465	505	525	555	595
Seat Tube C-C	-	-	-	-	-	-	-
BB Drop	72	72	72	70	70	70	70
BB Rise	-	-	-	-	-	-	-
CS	403	403	403	405	405	407	410
Front Center	573	575	577	585	591	606	621
Wheelbase	965	967	969	980	986	1003	1021
Standover	657	676	710	747	767	790	828
Fork Length	380	380	380	380	380	380	380
Rake	52	52	47	47	43	43	43
Lower HS Stack	1	1	1	1	1	1	1
Reach	362	369	377	385	394	405	414
Stack	499	512	530	550	572	594	621

## VERZA SPEED CARBON GEOMETRY

Size	43	45	51	54	56	58	61
HA	69	70	71	71	71	71	71
SA	74	73	73	73	72	72	72
TT Horiz	495	513	528	549	564	580	600
TT C-C	-	-	-	-	-	-	-
HT Length	120	130	140	160	180	200	220
Seat Tube C-T	430	450	470	500	520	540	570
Seat Tube C-C	375	395	415	425	445	465	495
BB Drop	64	64	64	64	65	65	65
BB Rise	-	-	-	-	-	-	-
CS	438	438	445	445	445	445	445
Front Center	583	585	591	602	612	622	642
Wheelbase	1013	1015	1027	1038	1049	1058	1079
Standover	707	718	753	780	798	819	845
Fork Length	393	393	393	393	393	393	393
Rake	54	54	52	52	52	52	52
Lower HS Stack	1	1	1	1	1	1	1
Reach	345	352	360	369	372	376	389
Stack	524	537	550	571	590	610	629



## VERZA SPEED ALLOY GEOMETRY

Size	47	51	54	56	58	61	61
HA	70	70	70	70	70	70	74
SA	74	74	74	74	74	74	73
TT Horiz	540	555	570	585	600	620	604
TT C-C	-	-	-	-	-	-	-
HT Length	140	160	180	200	220	240	205
Seat Tube C-T	350	400	450	500	550	600	595
Seat Tube C-C	-	-	-	-	-	-	-
BB Drop	70	70	70	70	70	70	70
BB Rise	-	-	-	-	-	-	-
CS	445	445	445	445	445	445	410
Front Center	613	629	645	662	678	699	621
Wheelbase	1048	1064	1081	1097	1114	1135	1021
Standover	627	663	710	756	800	843	828
Fork Length	393	393	393	393	393	393	380
Rake	48	48	48	48	48	48	43
Lower HS Stack	1	1	1	1	1	1	1
Reach	381	390	400	410	419	434	414
Stack	555	574	593	612	631	649	621

## MEN'S CRUISER GEOMETRY

Size	26"			
HA	69			
SA	67			
TT Horiz	650			
TT C-C	-			
HT Length	130			
Seat Tube C-T	465			
Seat Tube C-C	-			
BB Drop	45			
BB Rise	-			
CS	529			
Front Center	671			
Wheelbase	1198			
Standover	753			
Fork Length	405			
Rake	55			
Lower HS Stack	12			
Reach	422			
Stack	536			

## WOMEN'S CRUISER GEOMETRY

Size	26"			
HA	69			
SA	67			
TT Horiz	530			
TT C-C	-			
HT Length	130			
Seat Tube C-T	425			
Seat Tube C-C	-			
BB Drop	45			
BB Rise	-			
CS	530			
Front Center	651			
Wheelbase	1178			
Standover	489			
Fork Length	405			
Rake	55			
Lower HS Stack	12			
Reach	402			
Stack	536			

## TK GEOMETRY

Size	52	55	57	60		
HA	73	73.5	74	74.5		
SA	74	74	74	73.5		
TT Horiz	530	550	570	600		
TT C-C	530	550	570	600		
HT Length	80	90	110	135		
Seat Tube C-T	505	525	545	570		
Seat Tube C-C	455	475	495	520		
BB Drop	55	55	55	55		
BB Rise	-	-	-	-		
CS	375	375	375	375		
Front Center	566	582	598	619		
Wheelbase	935	950	967	987		
Standover	745	754	774	800		
Fork Length	365	365	365	365		
Rake	40	40	40	40		
Lower HS Stack	1	1	1	1		
Reach	395	412	426	444		
Stack	469	480	501	527		

## IA GEOMETRY

Size	48	51	54	56	58	
HA	71.5	71.5	72	72	72	
SA	79.5	79	78.5	78	77.5	
TT Horiz	468	486	510	541	573	
TT C-C	-	-	-	-	-	
HT Length	67.5	96	111	136	163	
Seat Tube C-T	496	525	546	571	598	
Seat Tube C-C	-	-	-	-	-	
BB Drop	72	72	72	72	72	
BB Rise	-	-	-	-	-	
CS	408.5	408.5	408.5	408.5	408.5	
Front Center	572	589	602	630	659	
Wheelbase	969.5	986.5	999.5	1028.5	1057.5	
Standover	744	776	790	819	840	
Fork Length	376	376	376	376	376	
Rake	50	50	45	45	45	
Lower HS Stack	1	1	1	1	1	
Reach	381	389	405	426	447	
Stack	473	501	520	544	569	

## B GEOMETRY

Size	51	54	56	58	61	
HA	72.5	73	73	73	73	
SA	76	76	76	76	76	
TT Horiz	518	539	559	579	594	
TT C-C	515	540	560	580	594	
HT Length	115	127	147	167	198	
Seat Tube C-T	510	540	560	580	610	
Seat Tube C-C	-	-	-	-	-	
BB Drop	70	70	70	70	70	
BB Rise	-	-	-	-	-	
CS	395	395	395	395	395	
Front Center	577	593	614	635	652	
Wheelbase	961	978	999	1020	1037	
Standover	743	764	779	780	780	
Fork Length	370	370	370	370	370	
Rake	40	40	40	40	40	
Lower HS Stack	1	1	1	1	1	
Reach	388	405	420	436	444	
Stack	521	535	554	573	602	



## BROAM GEOMETRY

Size	47	51	54	56	58	61
HA	70.5	70.5	71	71	71	71
SA	74	74	74	73	73	73
TT Horiz	530	535	555	570	580	595
TT C-C	512	517	534	546	557	572
HT Length	125	145	165	180	200	220
Seat Tube C-T	410	435	460	485	515	545
Seat Tube C-C	365	391	416	442	472	502
BB Drop	72	72	72	72	72	72
BB Rise	-	-	-	-	-	-
CS	450	450	450	450	450	450
Front Center	599	605	616	626	636	652
Wheelbase	1039	1045	1056	1066	1076	1092
Standover	688	713	720	762	790	818
Fork Length	400	400	400	400	400	400
Rake	50	50	50	50	50	50
Lower HS Stack	1	1	1	1	1	1
Reach	372	372	380	385	389	398
Stack	551	570	591	605	324	643





## BREED GEOMETRY

Size	47	51	54	56	58	61
HA	70	70.5	70.5	71	71.5	71.5
SA	74	74	74	73	73	72
TT Horiz	530	540	555	570	585	600
TT C-C	506	516	531	544	558	573
HT Length	130	135	150	165	180	200
Seat Tube C-T	440	470	500	520	540	570
Seat Tube C-C	397	516	531	544	558	573
BB Drop	72	72	72	72	72	72
BB Rise	-	-	-	-	-	-
CS	420	420	420	420	420	420
Front Center	603	610	620	625	629	639
Wheelbase	1013	1019	1030	1035	1039	1048
Standover	687	708	737	757	777	805
Fork Length	400	400	400	400	400	400
Rake	50	50	50	50	50	50
Lower HS Stack	1	1	1	1	1	1
Reach	374	379	385	389	394	397
Stack	544	561	575	591	607	626





## FX GEOMETRY

Size	47	50	53	55	57	60
HA	70.5	70.5	71	72	72	72
SA	75.5	74.5	73.5	73.5	73.5	73.5
TT Horiz	515	530	545	565	580	600
TT C-C	501	515	530	548	563	583
HT Length	110	120	130	150	170	190
Seat Tube C-T	470	500	530	550	570	590
Seat Tube C-C	410	440	470	490	510	530
BB Drop	65	65	65	65	65	65
BB Rise	-	-	-	-	-	-
CS	430	430	430	430	430	430
Front Center	599	604	605	611	626	647
Wheelbase	1022	1028	1029	1033	1048	1068
Standover	726	750	775	796	815	834
Fork Length	393	393	393	393	393	393
Rake	50	50	50	45	45	45
Lower HS Stack	1	1	1	1	1	1
Reach	380	382	384	397	406	420
Stack	523	533	544	568	587	607



## EDICT GEOMETRY

Size	S (16)	M (18)	L (20)	XL (22)	
HA	70	70	70	70	
SA	74.3	74.3	74.3	74.3	
TT Horiz	573	599	625	650	
TT C-C	-	-	-	-	
HT Length	90	105	120	145	
Seat Tube C-T	405	450	495	540	
Seat Tube C-C	-	-	-	-	
BB Drop	45	45	45	45	
BB Rise	325	325	325	325	
CS	436	436	436	436	
Front Center	661	688	715	742	
Wheelbase	1093	1121	1148	1175	
Standover	690	726	745	767	
Fork Length	506	506	506	506	
Rake	51	51	51	51	
Lower HS Stack	1	1	1	1	
Reach	407	429	451	470	
Stack	589	603	617	640	

## DOCTRINE GEOMETRY

Size	14	16	18	20	22	
HA	69.5	69.5	69.5	69.5	69.5	
SA	73	73	73	73	73	
TT Horiz	568	590	612	634	656	
TT C-C						
HT Length	90	95	105	115	125	
Seat Tube C-T	360	400	451	502	554	
Seat Tube C-C	311	351	402	453	505	
BB Drop	61	65	65	65	65	
BB Rise	-	-	-	-	-	
CS	430	430	430	430	430	
Front Center	644	665	688	710	733	
Wheelbase	1066	1087	1109	1132	1155	
Standover	683	714	757	799	841	
Fork Length	506	506	506	506	506	
Rake	51	51	51	51	51	
Lower HS Stack	1	1	1	1	1	
Reach	384	403	422	441	461	
Stack	602	611	620	630	639	



## DISPATCH GEOMETRY

Size	14	16	18	20	22	
HA	69	69	69	69	69	
SA	73	73	73	73	73	
TT Horiz	563	585	607	629	651	
TT C-C	-	-	-	-	-	
HT Length	95	100	110	120	130	
Seat Tube C-T	380	425	470	515	560	
Seat Tube C-C	-	-	-	-	-	
BB Drop	65	65	65	65	65	
BB Rise	-	-	-	-	-	
CS	445	445	445	445	445	
Front Center	644	666	688	711	734	
Wheelbase	1080	1103	1126	1148	1171	
Standover	693	730	769	806	842	
Fork Length	506	506	506	506	506	
Rake	51	51	51	51	51	
Lower HS Stack	1	1	1	1	1	
Reach	377	397	417	436	455	
Stack	609	613	623	632	641	



## DECREE GEOMETRY

Size	S (16)	M (18)	L (20)	XL (22)		
HA	66.5	66.5	66.5	66.5		
SA	73	73	73	73		
TT Horiz	565	597	627	657		
TT C-C	560	581	602	628		
HT Length	90	105	125	145		
Seat Tube C-T	395	430	485	540		
Seat Tube C-C	295	330	385	440		
BB Drop	9	9	9	9		
BB Rise	340	340	340	340		
CS	428	428	428	428		
Front Center	680	712	744	776		
Wheelbase	1108	1140	1172	1204		
Standover	694	725	774	822		
Fork Length	539	539	539	539		
Rake	42	42	42	42		
Lower HS Stack	12	12	12	12		
Reach	386	412	436	460		
Stack	580	594	612	631		



## COMPULSION GEOMETRY

Size	S (16)	M (18)	L (20)	XL (22)	
HA	65	65	65	65	
SA	74.4	74.4	74.4	74.4	
TT Horiz	568	597	627	654	
TT C-C	-	-	-	-	
HT Length	90	105	125	150	
Seat Tube C-T	405	435	470	505	
Seat Tube C-C	-	-	-	-	
BB Drop	10	10	10	10	
BB Rise	340	340	340	340	
CS	433	433	433	433	
Front Center	723	754	788	819	
Wheelbase	1154	1187	1221	1252	
Standover	708	722	735	750	
Fork Length	560	560	560	560	
Rake	46	46	46	46	
Lower HS Stack	4	4	4	4	
Reach	405	430	455	475	
Stack	583	597	615	638	



## DD GEOMETRY

Size	Small	Medium	Large		
HA	70	70	70		
SA	73	73	73		
TT Horiz	580	610	640		
TT C-C	562	586	615		
HT Length	105	120	135		
Seat Tube C-T	406	470	533		
Seat Tube C-C	-	-	-		
BB Drop	65	65	65		
BB Rise	-	-	-		
CS	455	455	455		
Front Center	642	673	704		
Wheelbase	1090	1120	1151		
Standover	720	775	825		
Fork Length	468	468	468		
Rake	45	45	45		
Lower HS Stack	12	12	12		
Reach	396	422	448		
Stack	599	613	628		

## Q GEOMETRY

Size	Q20-S	Q24	Q24 Disc		
HA	69	69	69		
SA	70	70	70		
TT Horiz	440	525	525		
TT C-C	420	504	504		
HT Length	104	110	110		
Seat Tube C-T	250	285	285		
Seat Tube C-C	204	239	239		
BB Drop	-8	23	23		
BB Rise	8	-	-		
CS	390	410	410		
Front Center	484	559	559		
Wheelbase	874	968	968		
Standover	529	580	580		
Fork Length	460	460	460		
Rake	30	30	30		
Lower HS Stack	12	12	12		
Reach	250	322	322		
Stack	519	556	556		